

Meersbloem Melden 16
9700 Oudenaarde - Belgium
T : + 32 55 31 83 35
F : + 32 55 31 43 88
www.vergokan.com

Integral cable trays with a height of 110 mm, hot-dip galvanized according to EN ISO 1461

The cable trays are made of perforated steel plate with rounded edges and a wing height of 110 mm. After having been manufactured, they are galvanized by means of immersion, in accordance with the EN ISO 1461 norm with a zinc layer of 50 to 80 micron. The elements are assembled with prefabricated pieces and screws and bolts with rounded heads.

The cable trays have been perforated with pressed-in alternative perforations of 7 x 25 mm and perforations in the central shaft with a diameter of 16 mm and 19.5 mm for cable passages.

The cable trays have a thickness of 1.50 mm and are available in widths of 200 mm, 300 mm, 400 mm, 500 mm and 600 mm. The elements have a standard length of 6000 mm and a maximum allowed load of 40 kg/m (uniformly divided) at a range of 6 metres.

Accessories like brackets, corner pieces, screws, T-pieces, assembly accessories and bends, are from the same manufacturer and of the same quality.

The supports are made in such a way that one side remains free, so that new cables can be added there without these having to be stuck between the supports.

The cable trays are attached with hard wall brackets and/or ceiling supports and/or on suspension brackets and hard brackets with regular intervals and in a sufficiently large number in order to prevent any deformation of the construction and of the cable installation.

The maximum distance between two ceiling supports and brackets is chosen in function of the maximum load and the maximum deflection, tested by the manufacturer according NBN EN 61.537. The maximum distance is limited to 6 metres.

Brand: Vergokan or similar.

These specifications are valid only in Belgium. Products meet with the charge book 400

VERGOKAN NV
BTW/TVA BE 0422.878.131
RPR OUDENAARDE

ING 390-0638604-11
IBAN BE30 3900 6386 0411
BIC BBRUBEBB