

Meersbloem Melden 16  
9700 Oudenaarde - Belgium  
T : + 32 55 31 83 35  
F : + 32 55 31 43 88  
[www.vergokan.com](http://www.vergokan.com)

## Cable trays with a height of 85 mm, hot-dip galvanized according to EN ISO 1461

The cable trays are made of perforated steel plate with rounded edges and a wing height of 85 mm. After having been manufactured, they are galvanized by means of immersion, in accordance with the EN ISO 1461 norm with a zinc layer of 50 to 80 micron. The elements are assembled with prefabricated pieces and screws and bolts with rounded heads.

The cable trays have been perforated with pressed-in alternative perforations of 7 x 25 mm and perforations in the central shaft with a diameter of 16 mm and 19.5 mm for cable passages.

The cable trays have a thickness of 1.0 mm for widths up to 300 mm, 1.00 mm or 1.50 mm for widths of 400 mm and 1.25 or 1.50 mm for widths of 500 and 600 mm. The standard elements have a length of 3000 mm.

Accessories like brackets, corner pieces, screws, T-pieces, assembly accessories, and bends, are from the same manufacturer and of the same quality.

The supports are made in such a way that one side remains free, so that new cables can be added there without these having to be stuck between the supports.

The cable trays are attached with hard wall brackets and/or ceiling supports and hard brackets with regular intervals and in a sufficiently large number in order to prevent any deformation of the construction and of the cable installation.

The maximum distance between two ceiling supports, brackets or suspension brackets is chosen in function of the maximum load and the maximum deflection, tested by the manufacturer according to NBN EN 61.537. The maximum distance is limited to 3 metres.

Brand: Vergokan or similar.

*These specifications are valid only in Belgium. Products meet with the charge book 400*

VERGOKAN NV  
BTW/TVA BE 0422.878.131  
RPR OUDENAARDE

ING 390-0638604-11  
IBAN BE30 3900 6386 0411  
BIC BBRUBEBB