

Meersbloem Melden 16
9700 Oudenaarde - Belgium
T : + 32 55 31 83 35
F : + 32 55 31 43 88
www.vergokan.com

Heavy integral industrial cable ladders, hot-dip galvanized according to EN ISO 1461 Ladders in the KLIS (KLI Samson) series

Construction

The cable ladders are composed of 2 side walls of 125 mm high and 25 mm wide and round hollow rung with a diameter of 19 mm.

The useful inner height is 95 mm.

The rungs have been doubly fixed every 250 mm at the flanges in the side walls.

The ladders are available in lengths of 6 metres and in widths of 200, 300, 400, 500 and 600 mm.

The cable ladders are hot-dip galvanized by immersion (after manufacturing), in accordance with the EN ISO 1461 norm. Thickness of the zinc layer is between 50 and 80 micron.

The several lengths and the accessories (bends, T-pieces, cross-overs, bends) are assembled using jointing plates with a form that has been adapted to the form of the side walls.

There are two types of jointing plates available:

- A standard jointing plate with a length of 220 mm that has two pressure screws for quick and robust assembly, for ranges of less than 5 metres.
- A jointing plate with a large range and with a length of 1,000 mm that has 4 pressure screws for quick and robust assembly of 5 meters and more (maximum 6 metres).

Allowed load

The allowed load with a range of 6 metres: 85 kg/m, continuously mounted, uniformly shared loads, mounting of the jointing plates without the supports on 1/5th of the range, safety coefficient = 2, deflection 1/200.

Depending on the requisites for the course of action to be taken, there are reducing plates, vertical and horizontal hinges, branch hooks and foot rests.

Meersbloem Melden 16
9700 Oudenaarde - Belgium
T : + 32 55 31 83 35
F : + 32 55 31 43 88
www.vergokan.com

Depending on the application, the ladders can be attached with wall supports, wall brackets, etc. The ladders are mounted on the wall brackets with adjusted brackets clamps.

The covers are attached with clips.

Brand: Vergokan or similar.

These specifications are valid only in Belgium. Products meet with the charge book 400