

Meersbloem Melden 16  
9700 Oudenaarde - Belgium  
T : + 32 55 31 83 35  
F : + 32 55 31 43 88  
[www.vergokan.com](http://www.vergokan.com)

## Floor installations countersunk in the coating

### General

The installation complies with the regulations of the AREI and the regulations for telecommunications and data transmission circuits.

The supply comprises the floor trunking, the floor boxes for the fastening and the connection of the floor trunking and the boxes, the accessories for finishing on carpets, vinyl, parquet or tiles, and the mounting units for the connections.

### Construction

The floor installations are made out of steel plate and galvanized according to the Sendzimir procedure. They are delivered in standard lengths of 3,000 mm.

The floor installations have the following dimensions:

- 28 x 170 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 28 x 250 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 28 x 350 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 28 x 370 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
  
- 38 x 170 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 38 x 250 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 38 x 350 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 38 x 370 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
  
- 48 x 170 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 48 x 250 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 48 x 350 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)
- 48 x 370 mm, 2 compartments (1/2-1/2) or 3 compartments (1/3-1/3-1/3)

The floor trunking with a rectangular diameter are composed of a base profile with a thickness of 1 mm and a cover in steel plate with a thickness of 1.5 mm, folded in U-form.

The base and the cover are connected to each other with a locking ring every 480 mm from the edge.

The channels have spot welded sections.

*These specifications are valid only in Belgium. Products meet with the charge book 400*