


COMEGACL 170

Snap-in suspension bracket for VF/VFL



Useful for direct mounting to the ceiling or with threaded rod TIM 8 or TIM 10.

Width	Max. load (in daN)	A
150	60	147
200	60	172
300	50	222
400	40	272

On Demand	Powder coating
Standard finish	Pre-galvanised
Optional finish 1	Hot-dip galvanised

1	Reference	Height	Width	Thickness	Length	kg/piece	Packaging	Stock	Unit
HD	- COMEGACL 170*150	170	182	-	-	0,46	10	✓	piece
HD	- COMEGACL 170*200	170	232	-	-	0,54	10	✓	piece
HD	- COMEGACL 170*300	170	332	-	-	0,70	10	✓	piece
HD	- COMEGACL 170*400	170	432	-	-	0,86	10	✓	piece

To use with :

COMEGACL 170*150 :
VF(L) 35*100, VF(L) 35*150, VF(L) 60*100, VF(L) 60*150

COMEGACL 170*200 :
VF(L) 35*150, VF(L) 60*150, VF(L) 60*200

COMEGACL 170*300 :
VF(L) 35*200, VF(L) 35*250, VF(L) 60*200, VF(L) 60*300

COMEGACL 170*400 :
VF(L) 35*350, VF(L) 60*300, VF(L) 60*400

Max. load (in daN) : uniformly distributed over complete width of cantilever brackets.