

3. CONCRETE FLOOR SYSTEMS - FLOOR FINISH WITH CORRESPONDING HINGED COVERS

PANDORA V - Floorbox square

Floor finish	Material	Application	To standard	Depth of cover cut-out	Description	Code	Accessories	Compartments
Carpet Vinyl Epoxy	Polypropylene RAL 7011 RAL 9011	Outlet	IP 20 (IP 30)*	5 mm	Hinged cover square	KDV 5*257		max. 3 TSB / TSBCL / 1x TSB 65
					Hinged cover round	KDR 5*257		
		Blind	IP 30	Blind cover square	BDV 5*257	max. 2 TSB / TSBCL		
				Blind cover round	BDR 5*257			
Tile Wooden laminated Polished concrete	Stainless steel	Outlet	IP 20 (IP 30)*	16 mm	Hinged cover square	IKDV 16*257	IKDVZ 6 - Metal plate for heavy loads	max. 3 TSB / TSBCL / 1x TSB 65
				26 mm	Hinged cover square	IKDV 26*257		
		Blind	IP 55	13 mm	Blind cover for tiled floor	ITKV 13*257	ITKVZ 6 - Metal plate for heavy loads	
				23 mm	Blind cover for tiled floor	ITKV 23*257		
		Outlet	watertight up to 30 mm IP 53 (IP 55)*	12 mm	Hinged cover square water resistant	KDVWD 12*257	TWD Tube AHWD Cover housing ITKVWDZ 6 - Metal plate for heavy loads	max. 3 TSB / TSBCL / 1x TSB 65
				13 mm	Hinged cover square water resistant	ITKVWD 13*257		
23 mm	Tile-cassette square water resistant			ITKVWD 23*257				

* When inactive

PANDORA R - Floorbox round

Floor finish	Material	Application	To standard	Depth of cover cut-out	Description	Code	Colours	Compartments
Carpet Vinyl Epoxy	Polypropylene	Outlet	IP 20 (IP 30)*	6 - 8 mm	Hinged cover round	KDRV 6*304	RAL 7011 RAL 9011	max. 3 TSB / TSBCL
					Blind cover round	BDRV 11*304		

TSB 65 is ideally placed in a PANDORA V 28*257.

TSB / TSBCL = minimal height of 78 mm of concrete floor
TSB 65 = minimal height of 65 mm of concrete floor