



TECHNICAL INFO

TECHNICAL INFO

SELECTION TABLE : Type of Surface Treatments related to the Corrosion Class and Risks per type of Environment (EN ISO 14713)

Corrosion Class - Risk + Average zinc loss per year	Surface treatments	Typical environment - Indoor	Typical environment - Outdoor
C1 - Very low < 0,1 µm	Electro-galvanisation EN ISO 2081	Heated buildings with neutral atmospheres : offices, shops, schools, hotels.	Rural areas. Atmosphere with low impurities. 
C2 - Low 0,1-0,7 µm	Pre-galvanisation (SZ) Sendzimir galvanisation EN 10327 - EN 10 346	Unheated buildings where condensation may occur: warehouses, shops, sports halls.	
C3 - Medium 0,7 – 2,0 µm	Hot-dip galvanisation (HD) EN ISO 1461	Production facilities with high moisture levels and some air impurities : plants for food production, laundries, breweries, dairies.	
C4 - High 2,0 – 4,0 µm	Hot-dip galvanisation (HD) EN ISO 1461	Chemical plants, swimming pools, boathouses above sea water.	
C5-I - Very high (industry) 4,2 – 8,4 µm	Duplex (HD + Powder Coating) Stainless steel AISI 316L	Buildings or areas with almost constant condensation and with heavy impurities.	
C5-M - Very high (sea) >4,2 – 8,4 µm	Duplex (HD + Powder Coating) Stainless steel AISI 316L	Buildings or areas with almost constant condensation and with heavy impurities.	
			Coastal or offshore areas with salt load.

SURFACE TREATMENTS

Sendzimir galvanised EN 10..346

Ref. : SZ

Most of the cable trunkings, accessories and threaded rod fixings are made of Sendzimir galvanised steel, also called continuous galvanised steel.

The hot-rolled steel belt goes, after preparation, through a continuous bath with liquid zinc. Through this, a layer of zinc is formed which guarantees the increased corrosion protection. Depending on the product type the thickness of the zinc layer varies from 140 to 275 gr/m², bilaterally calculated. This corresponds to 10 to 20 µm with a tolerance of +/- 4 µm.

Through the special Sendzimir zinc process, the steel-engraving can still be very easily carried out even after galvanisation. During the fabrication of the cable trunkings, the steel-engraving and the belt are punched, cut and bent. The exposed steel-edges are cathodically protected till a material thickness of 1.5mm is reached, as far as the zinc-layer had not already been bent over it during manufacturing. Substrate rust does not occur.

For normal interior construction purposes the Sendzimir galvanised materials offer more than adequate protection against corrosion (covered parking areas, various uses indoors etc.).

Hot-dip galvanised EN ISO 1461

Ref. : HD

Many cable ladders, ceiling profiles and brackets are hot-dip galvanised. For this surface treatment, other various terms are used such as fire galvanisation, thermal galvanization etc.

The finished pieces are plunged in a melt-bath with liquid zinc, after pre-treatment, at a temperature $\geq +/ - 450^{\circ}\text{C}$. A layer of zinc and iron is formed on the steel, which is covered with a pure zinc layer after removal from the zinc bath.

The thickness of the zinc layer depends on the thickness (gauge) of the steel. The guidelines in accordance with EN ISO 1461 are followed:

Material thickness	minimum localized layer thickness (µm)	minimum average layer thickness (µm)
$\geq 6 \text{ mm}$	70	85
$\geq 3 \text{ mm} \text{ to } < 6 \text{ mm}$	55	70
$\geq 1.5 \text{ mm} \text{ to } < 3 \text{ mm}$	45	55
< 1.5 mm	35	45

Small Items are galvanised and centrifuged. With regard to this the specific guidelines recorded in EN ISO 1461 are followed:

Material thickness	minimum localized layer thickness (µm)	minimum average layer thickness (µm)
$\geq 3 \text{ mm}$	45	55
< 3 mm	35	45

The increased thickness of the zinc layer ensures a better resistance against corrosion compared to continuous galvanised steel. Hot dip galvanised steel is also more suited to outdoor applications.

The requirements for hot dipped galvanised products refer to:

- the coating thickness of the galvanised layer or to its mass per unit area
- the outward appearance of the surface coating

The coating thickness is the deciding factor for the wear life in well-defined operating conditions. The thicker the coating, the longer the expected wear life. For most atmospheric exposures, a near-linear relationship exists between the two.

The second requirement concerns the outward appearance of the coating. On that score, the relevant standard (EN ISO 1461) stipulates the following:

- Products on which darker or lighter grey areas occur, whose surface exhibits some surface roughness or on which white storage stains can be found, will still meet the standard EN ISO 1461, providing the coating thickness remains above the specified minimum value.
- Lumps and zinc ash are permitted in places where they do not affect the intended use of the hot dipped galvanised object or its corrosion resistance requirements

Electro zinc plated (EN ISO 2081)

The wire cable trays and all sorts of fixation elements are electro zinc plated.

During this procedure a thin zinc-layer is precipitated, varying in thickness between 6 and 8 microns, by means of an electrolytic process. After this the items are passivated and in this way protected against corrosion under normal indoor conditions.

Coated finishes

Our fully automated coating process applies a satin finish as standard. We can apply a high gloss, matt or textured coat on request.

Polyester powder coating (standard)

Ref : PE

The products we supply with a polyester powder coating finish easily meet the required standards. Polyester powder coating is suited to indoor and outdoor applications and offers a very high degree of resistance to all weather conditions.

Epoxy powder coating

Ref: EP

Epoxy coatings are characterised by their great resistance to both corrosion and chemicals. On the other hand epoxy powder coatings are not suitable for outside uses due to their poor resistance to UV light which results in degradation of the coating.

Epoxy powder coating + Polyester powder coating

Ref : EPPE

Epoxy is often used as a primer which will then have a polyester topcoat applied. This double layer coating results in a product that is both chemically and UV resistant.

Duplex System

Ref: DUPLEX

The combination of a hot-dip galvanizing and powder coating creates an extremely powerful protection against corrosion.

For technical advice and price inquiries, please consult our sales team. Delivery period of powder coated and duplex coated products is to be agreed upon in respect to volume and specifications.

VERGOKAN

Alphabetical list of references

Reference	Page	Reference	Page	Reference	Page	Reference	Page
A		DAS	1-24	HDAB35.110	7-413	HDMP41.41DG	5-267
ADPU	6-365	DAVIDKV	4-141	HDAB35.110	7-387	HDNL	4-143
ADPUB	6-365	DB90	1-22	HDABIE	4-155	HDRU1	4-208
ADSU	6-366	DBTFCL	2-54	HDAHIE	4-156	HDRU2	4-209
AM	6-361	DCL	4-105	HDBKID25	4-158	HDSKIPE	5-260
AS	1-24	DCL	1-20	HDBKIE25	4-157	HDSKP	5-258
ASTFCL	2-55	DCL	8-443	HDBKIE40	4-157	HDSSU	4-145
AZH	1-31	DCLVF	3-67	HDBSKLEM	7-392	HDTSU	7-415
		DCLVF	8-445	HDBSKLEM	7-414	HDTSU	5-255
B		DCLVF35	3-68	HDDI	4-151	HDVK2	4-144
B	5-274	DCO	1-20	HDDI	4-140	HDVS41	5-270
B	7-428	DGBTFCL	2-55	HDDIB	4-141	HDVS41	7-418
B90	1-21	DGTFCL	2-53	HDDIB	4-152	HDVS41	5-271
BDRITWD3	6-327	DKBS	7-416	HDDIB	4-106	HDVS41.05	7-413
BDRKK3	6-317	DKI	4-152	HDDIB	4-122	HDVS41.45	7-395
BDVITWD2	6-326	DKR	1-25	HDDIG	4-196	HDVSIE	4-157
BDVITWD3	6-326	DOP41.21	5-256	HDDIG	4-182	HDWK	5-242
BDVIZ	6-362	DOP41.41	5-257	HDDIG	4-166	HDWK	7-392
BDVKK2	6-315	DOP41.82	5-257	HDDIT	4-142	HDWK	7-413
BDVKK3	6-316	DOPHSMU	5-257	HDDIT	4-153	HDWKMD	5-247
BG	5-221	DOPPIPE80	5-259	HDDIT	4-123	HDWKMD	7-414
BGVF	3-72	DOPKLIE	4-158	HDDKIG	4-196	HDWVPIPE	5-261
BK	4-108	DOPKLL	8-461	HDDKIG	4-182	HSLE3	5-252
BK	7-386	DOPKLL	4-130	HDDKIG	4-166	HSMD	5-254
BP	4-154	DOPKLL60.M	4-131	HDDKIKE	5-261	HSMES	5-253
BP	4-203	DOPKLM	8-470	HDDSIH	4-156	HSMES	7-416
BP	4-189	DOPKLM	4-172	HDDSIV	4-156		
BP	4-173	DOPKLW	4-202	HDDSKSH	4-144	I	
BTFCL	2-54	DOPKLZ	8-479	HDH1	4-208	I4COMEGA290	8-481
BVSI	1-31	DOPKLZ	4-188	HDH1	7-389	I4D	8-439
C		DOPKS	4-145	HDH2	4-209	I4D	8-453
CBCL60	5-238	DOVG	6-336	HDHKI	5-248	I4KBSI60	8-437
CCLI	5-233	DOVGR.3	6-338	HDHKIZ	5-249	I4KG60	8-438
CL	1-35	DOVGV.2	6-337	HDHSIZ	5-256	I4KLL110	8-451
CLHS	5-251	DOVGV.3	6-337	HDHSLDCL	5-252	I4KLLDK	8-454
CLHS	7-418	DR15.30	5-222	HDHSLECL	5-251	I4KLLI60	8-449
CLHS	7-394	DR15.30	5-222	HDHSLECL	7-417	I4LOMEGA150	8-482
COMECA290	7-390	DR15.30	7-388	HDHSLECL	7-394	I4MP41.21.250.6S	8-485
COMECACLU170	3-74	DRITWD3	6-330	HDHSMD	5-254	I4MP41.41.250.6S	8-486
COMECACLU170	5-232	DS	1-30	HDHSMU50	7-415	I4VOMEGA	8-480
COMECACLU290	5-233	DS	4-109	HDHSMU50	5-255	I4WK	8-483
CRO	5-276	DSB90	1-27	HDIPE80S	5-258	I6AS	8-441
CRO	7-430	DT	1-23	HDIPL06	5-259	I6B	8-489
CS45LP	5-224	DTFCL	2-53	HDIPL10	5-259	I6B90	8-440
CS45M6	5-226	DVB90	1-29	HDKIPE	5-261	I6COMEGA290	8-481
CS45SH	5-225	DVITWD3	6-329	HDKK	4-144	I6CRO	8-489
CS45SHY	5-229	DZ	1-20	HDKLIB	4-152	I6D	8-453
CS45SHYA	5-228	DZK	1-21	HDKLIE	4-151	I6D	8-444
CS45TG	5-227	E	1-32	HDKLIT	4-153	I6D	8-439
CS90EY	5-226	F	5-219	HDKLIVSB	4-154	I6DAS	8-441
CS90LP	5-224	G		HDKLIX	4-154	I6DB90	8-440
CS90M8	5-226	GBP	6-368	HDKPIPE	5-260	I6DIG	8-472
CS90SH	5-225	GM	5-273	HDKS60	4-139	I6DIG	8-463
CS90SHY	5-229	GM41	5-273	HDKS90	4-141	I6DKIG	8-472
CS90SHYA	5-228	GMV41	5-273	HDKS90	4-140	I6DKIG	8-463
CS90TG	5-227	GVFUL	3-66	HDKS60	4-142	I6DS60	8-442
CSL	5-223	H		HDKS90	4-143	I6GM	8-487
D		HDAB35.110	4-108	HDKS90	4-143	I6GM41	8-487
D	4-104	HDAB35.110	4-130	HDLSVSB	4-143	I6HSLE	8-484
D	3-67			HDKSX	4-143	I6KBSI60	8-437
D	1-19			HDLVIE	4-159	I6KG60	8-438
D	4-120			HDLVIRL	4-155	I6KLL110	8-452
				HDLVIRR	4-155	I6KLLABD	8-454
				HDMBZ	5-235		
				HDMP41.21	5-265		
				HDMP41.41	5-266		

Reference	Page	Reference	Page	Reference	Page	Reference	Page
I6KLLAH	8-458	I6TIM	8-486	KLLBK	4-127	KLZSB	4-185
I6KLLAHV	8-458	I6V60.200	8-443	KLLCBL	5-239	KLZT	4-183
I6KLLB	8-455	I6VF60	8-444	KLLCBL	5-239	KLZVB	4-184
I6KLLBK	8-460	I6VFCB	8-447	KLLDK	4-120	KLZVS	4-187
I6KLLDK	8-454	I6VFK	8-445	KLLDSH	4-128	KLZVS	4-185
I6KLLDSH	8-459	I6VFG30	8-446	KLLDSV	4-129	KLZVST	4-187
I6KLLDSV	8-459	I6VFKK25	8-446	KLLI60	4-115	KLZX	4-184
I6KLLI60	8-450	I6VFKS	8-446	KLLI60.6	4-116	KPBS	7-385
I6KLLKP	8-460	I6VFM	8-447	KLLIBS60	7-411	KPBSKL	7-386
I6KLLSB	8-457	I6VMM	8-448	KLLKP	4-131	KPCL	5-249
I6KLLT	8-456	I6VFO	8-448	KLLSB	4-126	KPVF	3-78
I6KLLVB	8-457	I6VM	8-487	KLLT	4-123	KPVFL35	3-78
I6KLLVS	8-459	I6VMB	8-448	KLLVB	4-125	KPW	1-38
I6KLLVSB	8-458	I6VOMEGA	8-480	KLLVS	4-129	KR	1-25
I6KLLVST	8-460	I6WK	8-483	KLLVSB	4-127	KUWDT	6-330
I6KLLX	8-456	I6WSU	8-484	KLLVST	4-130	L	
I6KLM	8-462	IDP	6-367	KLLX	4-124	L25	5-262
I6KLMAH	8-467	K		KLM	4-165	L25.50	5-262
I6KLMAHV	8-467	KBS110	1-12	KLMAH	4-169	L50.50	5-262
I6KLMB	8-464	KBS110.6	1-13	KLMAHV	4-170	LBS	7-412
I6KLMDSH	8-468	KBS35	1-9	KLMB	4-167	LOMEGA150	7-389
I6KLMDSV	8-467	KBS60	1-10	KLMDSH	4-170	LOMEGACLU150	3-74
I6KLMKP	8-469	KBS60	7-385	KLMDSV	4-170	LOMEGACLU150	5-234
I6KLMMSB	8-466	KBS85	1-11	KLMKP	4-172	LV	1-39
I6KLMWT	8-464	KBSI35	1-6	KLMSB	4-169	LVBS60	7-387
I6KLMVB	8-465	KBSI60	1-7	KLMT	4-167	M	
I6KLMVS	8-468	KBSI60	7-411	KLMVB	4-168	M	5-275
I6KLMVSB	8-466	KBSI60.6	1-8	KLMVS	4-171	M	7-428
I6KLMVST	8-468	KBSM()60	1-14	KLMVSB	4-169	MK	6-369
I6KLMX	8-465	KBV	1-39	KLMVST	4-171	MP	1-33
I6KLMZWAB	8-478	KBV	8-443	KLMX	4-168	MP3.41.41	5-268
I6KLMZWAB	8-469	KCL	5-237	KLMZWAB	4-201	MP41.21	5-265
I6KLMZWABD	8-472	KCLBS	7-391	KLMZWAB	4-187	MP41.41	5-266
I6KLMZWABD	8-463	KDRKK3	6-320	KLMZWABD	4-170	MP41.41DG	5-267
I6KLMZWBK	8-478	KDRKK3	6-346	KLMZWABD	4-196	MPCL	7-417
I6KLMZWBK	8-469	KDVIRK2	6-347	KLMZWABD	4-182	MPCL	7-393
I6KLZ	8-471	KDVIRK2	6-321	KLMZWABD	4-166	MPCL41.21	5-250
I6KLZAH	8-476	KDVIRK3	6-322	KLMZWBK	4-172	MPV	1-33
I6KLZAHV	8-476	KDVIRK3	6-348	KLMZWBK	4-188	MPVCL	1-34
I6KLZB	8-473	KDVIT2	6-323	KLMZWBK	4-202	MPVFCL	3-73
I6KLZDHS	8-476	KDVIT3	6-324	KLT	4-107	N	
I6KLZDSV	8-477	KDVITV3	6-325	KLB	4-108	NATO15	1-19
I6KLZKP	8-478	KDVITWD3	6-328	KLW	4-195	NEO	6-312
I6KLZSB	8-475	KDVIZ	6-362	KLWAH	4-199	NEOAVT	6-360
I6KLZT	8-473	KDVKK2	6-344	KLWAHV	4-200	NEOT	6-360
I6KLZVB	8-474	KDVKK2	6-318	KLWB	4-197	O	
I6KLZVS	8-477	KDVKK3	6-345	KLWDSH	4-200	OBG	5-220
I6KLZVS	8-475	KDVKK3	6-319	KLWDSV	4-200	OBG	3-71
I6KLZVST	8-477	KG110	1-17	KLWKP	4-202	OBGVF	3-71
I6KLZX	8-474	KG110S	1-18	KLWSB	4-199	OBZ130	5-230
I6KPVF	8-445	KGI60	1-15	KLWT	4-197	OBZ180	5-231
I6LOMEGA150	8-482	KGI60S	1-16	KLWVB	4-198	OHE	6-361
I6M	8-489	KL60	4-103	KLWVS	4-201	OV	6-369
I6MP41.21.250.6S	8-485	KL60	7-387	KLWVB	4-199	OGV	6-336
I6MP41.41.250.6S	8-486	KLB	4-105	KLWST	4-201	OGGAN	6-341
I6PB	8-479	KLBS60	7-386	KLWX	4-198	OVGB	6-338
I6RB	8-488	KLL110	4-118	KLX	4-107	OVGE	6-340
I6RBK	8-488	KLL110.6	4-119	KLZ	4-181	OVGEQ	6-342
I6RM	8-488	KLL85	4-117	KLZAH	4-185	OVGEQH	6-343
I6RO	8-490	KLLABD	4-121	KLZAHV	4-186	OVGHV	6-342
I6SLOS	8-479	KLLAH	4-128	KLZB	4-183	OVGK	6-339
I6SLOS	8-470	KLLAHV	4-128	KLZDSH	4-186	OVGP	6-340
I6SLOS	8-442	KLLB	4-121	KLZDSV	4-186		
I6SLOS	8-461			KLZKP	4-188		

Alphabetical list of references

Reference	Page	Reference	Page	Reference	Page
OVGT	6-339	V15.200	1-35	WKCL	5-243
OVGTAP	6-342	V35	1-36	WKMP27.18	5-243
OVGTR	6-341	V35.200	1-37	WKMP41.21	5-244
OVGVST	6-341	V35.200	2-56	WKMP41.41	5-244
OVGZ	6-340	V35.200	3-78	WKMPCL41.21	5-244
P		V60	1-36	WKMPCL41.41	5-245
PBR	5-219	V60.200	1-37	WKS	5-240
Q		V60.200	4-109	WKSS	5-241
QL	7-412	V60.200	2-56	WKUMP41.41	5-245
R		V85	1-36	WKUMPCL41.41	5-246
RB	5-276	V85.200	1-38	WS	5-235
RBK	5-274	V85.200	2-56	WSUN	5-236
RBKBSM	1-33	VB90	1-28	Z	
RBS	5-278	VBCL	1-28	Z25	5-263
RM	5-276	VE	6-311	Z50	5-263
RO	5-277	VERP	6-314	ZCL	3-73
RO	7-430	VERV	6-313		
ROTD	5-277	VEVP	6-314		
S		VEVV	6-313		
SB90	1-26	VFCB	5-220		
SBCL	1-26	VFCB	3-70		
SDB	1-30	VFCL	3-70		
SDBG	5-219	VFK	3-76		
SKL60	4-104	VFGK30	3-77		
SKPD	5-268	VFKK25	3-77		
SKPE	5-268	VFKNIP	3-79		
SLIS	1-34	VFKS	3-77		
SLOS	1-34	VFM	3-69		
SLOS	3-76	VFMM	3-69		
SLOS	4-109	VFMM35	3-69		
SLOS	4-158	VFO	3-68		
SLOS	6-343	VFOCL	3-68		
SLOS	4-145	VFSLOSCL	3-76		
SLOS	4-131	VFU110	3-66		
SLOS	4-203	VFU35	3-63		
SLOS	4-189	VFU60	3-64		
SLOS	4-173	VFU85	3-65		
SSBU	6-366	VFUL35	3-61		
SYBS	7-388	VFUL60	3-62		
T		VFVLB	3-72		
T	1-23	VGI28	6-307		
TFCL110	2-52	VGI38	6-307		
TFCL110S	2-52	VGI48	6-308		
TFCL60	2-50	VGLI28	6-308		
TFCL60S	2-50	VGLI38	6-309		
TFCL85	2-51	VGLI48	6-310		
TFCL85S	2-51	VH	1-22		
TIM	5-271	VK	6-311		
TIM	7-418	VM	5-275		
TIM	7-395	VM	7-429		
TSBL	6-368	VM6334	5-272		
TSBU	6-363	VM6334	7-428		
TSBU45	6-363	VMB	5-230		
TSBU50	6-364	VMB	3-75		
TSBUD	6-364	VMK	5-275		
U		VMK	7-429		
U24	5-264	VOMEGA	5-234		
U48	5-264	VOMEGA	7-390		
V		VS	1-32		
V110.200	1-38	VS41	5-269		
		VSB	6-310		
		VSSPRAY	5-277		
		W			