

TECHNICAL INFO

TECHNICAL INFO

SELECTION TABLE : Type of surface treatments related to the corrosion class and risks per type of environment (EN ISO 14713-1/2010)

Corrosion Class - Risk + Average zinc loss per year	Surface treatments	Typical environment - Indoor	Typical environment - Outdoor
C1 - Very low < 0,1 µm	Electro-galvanisation EN ISO 2081	 	Dry or cold zone. Atmosphere with very low impurities. 
C2 - Low 0, 1-0,7 µm	Indoor : (SZ) Sendzimir galvanisation EN 10327 - EN 10.143 Outdoor : Hot-dip (HD) galvanisation EN ISO 1461		Unheated buildings where condensation may occur: warehouses, shops, sports halls. 
C3 - Medium 0,7 – 2 µm	Hot-dip galvanisation (HD) EN ISO 1461		Production facilities with high moisture levels and some air impurities : plants for food production, laundries, breweries, dairies. 
C4 - High 2 – 4 µm	Duplex: Hot-dip galvanisation (HD) EN ISO 1461 + 1 or 2 layers powder coating		Chemical plants, swimming pools, boathouses above sea water. 
C5-I - Very high (industry) 4 – 8 µm	Duplex : HD galvanisation + 2 layers powder coating thickness on demand Stainless steel AISI 316L		Buildings or areas with almost constant condensation and with high pollution. 
C5-M - Very high (sea) 4 – 8 µm	Duplex: HD galvanisation + 2 layers powder coating thickness on demand Stainless steel AISI 316L		Buildings or areas with almost constant condensation and with high pollution. 
			Coastal or offshore areas with salt load. 

SURFACE TREATMENTS

Sendzimir galvanised EN 10..346

Ref. : SZ

Most of the cable trunkings, accessories and threaded rod fixings are made of Sendzimir galvanised steel, also called continuous galvanised steel.

The hot-rolled steel belt goes, after preparation, through a continuous bath with liquid zinc. Through this, a layer of zinc is formed which guarantees the increased corrosion protection. Depending on the product type the thickness of the zinc layer varies from 140 to 275 gr/m², bilaterally calculated. This corresponds to 10 to 20 µm with a tolerance of +/- 4 µm.

Through the special Sendzimir zinc process, the steel-engraving can still be very easily carried out even after galvanisation. During the fabrication of the cable trunkings, the steel-engraving and the belt are punched, cut and bent. The exposed steel-edges are cathodically protected till a material thickness of 1.5mm is reached, as far as the zinc-layer had not already been bent over it during manufacturing. Substrate rust does not occur.

For normal interior construction purposes the Sendzimir galvanised materials offer more than adequate protection against corrosion (covered parking areas, various uses indoors etc.).

Hot-dip galvanised EN ISO 1461

Ref. : HD

Many cable ladders, ceiling profiles and brackets are hot-dip galvanised. For this surface treatment, other various terms are used such as fire galvanisation, thermal galvanization etc.

The finished pieces are plunged in a melt-bath with liquid zinc, after pre-treatment, at a temperature \geq +/- 450°C. A layer of zinc and iron is formed on the steel, which is covered with a pure zinc layer after removal from the zinc bath.

The thickness of the zinc layer depends on the thickness (gauge) of the steel. The guidelines in accordance with EN ISO 1461 are followed:

Material thickness	minimum localized layer thickness (µm)	minimum average layer thickness (µm)
≥ 6 mm	70	85
≥ 3 mm to < 6 mm	55	70
≥ 1.5 mm to < 3 mm	45	55
< 1.5 mm	35	45

Small Items are galvanised and centrifuged. With regard to this the specific guidelines recorded in EN ISO 1461 are followed:

Material thickness	minimum localized layer thickness (µm)	minimum average layer thickness (µm)
≥ 3 mm	45	55
< 3 mm	35	45

The increased thickness of the zinc layer ensures a better resistance against corrosion compared to continuous galvanised steel. Hot dip galvanised steel is also more suited to outdoor applications.

The requirements for hot dipped galvanised products refer to:

- the coating thickness of the galvanised layer or to its mass per unit area
- the outward appearance of the surface coating

The coating thickness is the deciding factor for the wear life in well-defined operating conditions. The thicker the coating, the longer the expected wear life. For most atmospheric exposures, a near-linear relationship exists between the two.

The second requirement concerns the outward appearance of the coating. On that score, the relevant standard (EN ISO 1461) stipulates the following:

- Products on which darker or lighter grey areas occur, whose surface exhibits some surface roughness or on which white storage stains can be found, will still meet the standard EN ISO 1461, providing the coating thickness remains above the specified minimum value.
- Lumps and zinc ash are permitted in places where they do not affect the intended use of the hot dipped galvanised object or its corrosion resistance requirements

Electro zinc plated (EN ISO 2081)

Various mounting systems are electro zinc plated.

During this procedure a thin zinc-layer is precipitated, varying in thickness between 6 and 8 microns, by means of an electrolytic process. After this the items are passivated and in this way protected against corrosion under normal indoor conditions.

Coated finishes

Our fully automated coating process applies a satin finish as standard. We can apply a high gloss, matt or textured coat on request.

Polyester powder coating (standard)

Ref : PE

The products we supply with a polyester powder coating finish easily meet the required standards. Polyester powder coating is suited to indoor and outdoor applications and offers a very high degree of resistance to all weather conditions.

Epoxy powder coating

Ref: EP

Epoxy coatings are characterised by their great resistance to both corrosion and chemicals. On the other hand epoxy powder coatings are not suitable for outside uses due to their poor resistance to UV light which results in degradation of the coating.

Epoxy powder coating + Polyester powder coating

Ref : EPPE

Epoxy is often used as a primer which will then have a polyester topcoat applied. This double layer coating results in a product that is both chemically and UV resistant.

Duplex System

Ref: DUPLEX

The combination of a hot-dip galvanizing and powder coating creates an extremely powerful protection against corrosion.

For technical advice and price inquiries, please consult our sales team. Delivery period of powder coated and duplex coated products is to be agreed upon in respect to volume and specifications.

Alphabetical list of references

Reference	Page	Reference	Page	Reference	Page	Reference	Page
A		D	4-113	GM41	7-456	HDKSX	4-150
ADPU	6-388	D	3-74	GMV41	5-280	HDLVIE	4-167
ADPUB	6-388	D	1-20	GVFUL	3-73	HDLVIRL	4-163
ADSU	6-389	DAS	4-129	H		HDLVIRR	4-163
AM	6-383	DAVIDKV	1-25	HDAB35.110	4-116	HDMBZ	5-245
AS	1-25	DB90	4-148	HDAB35.110	4-137	HDMP41.21	5-272
ASTFCL	2-60	DBTFCL	1-23	HDAB35.110	7-436	HDMP41.41	5-273
ASTSBL	6-391	DCL	2-59	HDAB35.110	7-410	HDMP41.41DG	5-274
AZH	1-31	DCL	4-114	HDABIE	4-163	HDNL	4-150
B		DCL	1-21	HDAHIE	4-164	HDRU1	4-218
B	5-281	DCL	8-472	HDBKID25	4-166	HDRU2	4-219
B	7-455	DCLVF	3-74	HDBKIE25	4-165	HDSKIPE	5-267
B90	1-22	DCLVF	8-474	HDBKIE40	4-165	HDSKP	5-265
BDRITWD3	6-345	DCLVF35	3-75	HDBSKLEM	7-415	HDSSU	4-152
BDRKK3	6-357	DCO	1-21	HDBSKLEM	7-437	HDTSU	7-438
BDRKK3	6-329	DGBTFCL	2-59	HDDI	4-159	HDTSU	5-262
BDVITWD2	6-339	DGTFCL	2-58	HDDI	4-147	HDUKPIM	5-255
BDVITWD3	6-340	DKBS	7-439	HDDIB	4-148	HDVK2	4-151
BDVIZ	6-385	DKI	4-160	HDDIB	4-160	HDVS41	7-441
BDVKK2	6-351	DKR	1-26	HDDIB	4-114	HDVS41	5-278
BDVKK2	6-325	DOP41.21	5-263	HDDIB	4-130	HDVS41.00-39	5-277
BDVKK3	6-354	DOP41.41	5-264	HDDIG	4-205	HDVS41.05	7-436
BDVKK3	6-327	DOP41.82	5-264	HDDIG	4-190	HDVS41.45	7-418
BG	5-231	DOPHSMU	5-264	HDDIG	4-174	HDVSIE	4-165
BGVF	3-79	DOPPIPE80	5-266	HDDIT	4-149	HDWK	5-249
BK	4-116	DOPKLIE	4-166	HDDIT	4-161	HDWK	7-415
BK	7-409	DOPKLL	8-490	HDDIT	4-131	HDWK	7-436
BP	4-162	DOPKLL	4-137	HDDKIG	4-205	HDWKM	5-254
BP	4-197	DOPKLL60.M	4-138	HDDKIG	4-190	HDWKM	7-437
BP	4-212	DOPKLM	8-499	HDDKIG	4-174	HDWKMD	5-254
BP	4-181	DOPKLM	4-180	HDDKIKE	5-268	HDWPIPE	5-268
BTFCL	2-58	DOPKLW	4-211	HDDSIH	4-164	HSLE3	5-259
BVSI	1-31	DOPKLZ	8-508	HDDSVI	4-164	HSMD	5-261
C		DOPKLZ	4-196	HDDSKSH	4-151	HSMES	5-260
CCLI	5-243	DOPKS	4-152	HDH1	4-218	HSMES	7-439
CL	1-35	DOVG	6-363	HDH1	7-412	I	
CLHS	5-258	DOVGR.3	6-364	HDH2	4-219	I4COMEGA290	8-510
CLHS	7-441	DOVGV.2	6-363	HDHKI	5-255	I4D	8-468
CLHS	7-417	DOVGV.3	6-363	HDHKIZ	5-256	I4D	8-482
COMEAGA290	7-413	DR15.30	5-232	HDHSIZ	5-263	I4KBSI	8-464
COMEAGACLU170	3-81	DR15.30	7-411	HDHSLDCL	5-259	I4KG60	8-466
COMEAGACLU170	5-242	DR21.41	5-233	HDHSLECL	5-258	I4KLL110	8-480
COMEAGACLU290	5-243	DRIT3	6-336	HDHSLECL	7-440	I4KLLDK	8-482
COMEAGACLU290	3-82	DRITWD3	6-346	HDHSLECL	7-417	I4KLLI60	8-478
CRO	5-283	DS	1-30	HDHSMD	5-261	I4LOMEGA150	8-511
CRO	7-457	DS	4-117	HDHSMU50	7-438	I4MP41.21	8-514
CS45LP	5-234	DSB90	1-28	HDHSMU50	5-262	I4MP41.41	8-515
CS45M6	5-236	DT	1-24	HDPIPE80S	5-265	I4VOMEGA	8-509
CS45SH	5-235	DTFCL	2-57	HDIPLO6	5-266	I4WK	8-512
CS45SHY	5-239	DVB90	1-29	HDIPLO10	5-266	I6AS	8-470
CS45SHYA	5-238	DVITWD3	6-341	HDKIPE	5-268	I6B	8-518
CS45TG	5-237	DVITWDV3	6-342	HDKK	4-151	I6B90	8-468
CS90EY	5-236	DZ	1-21	HDKLIB	4-160	I6COMEGA290	8-511
CS90LP	5-234	DZK	1-22	HDKLIE	4-159	I6CRO	8-518
CS90M8	5-236	E		HDKLIT	4-161	I6D	8-482
CS90SH	5-235	E	1-32	HDKLIVSB	4-162	I6D	8-473
CS90SHY	5-239	F		HDKLIX	4-162	I6D	8-468
CS90SHYA	5-238	FL	5-229	HDKPIPE	5-267	I6DAS	8-470
CS90TG	5-237	G		HDKS60	4-146	I6DB90	8-469
CSL	5-233	GBP	6-390	HDKS90	4-148	I6DIG	8-501
D		GM	5-280	HDKS60	4-147	I6DIG	8-492
		GM41	5-280	HDKST	4-149	I6DKIG	8-501
				HDKS90	4-150	I6DKIG	8-492

Reference	Page	Reference	Page	Reference	Page	Reference	Page
I6DS60	8-471	I6RB	8-517	KDVKK3	6-355	KLWSB	4-208
I6GM	8-516	I6RBK	8-517	KDVKK3	6-328	KLWT	4-206
I6GM41	8-516	I6RM	8-517	KG110	1-18	KLWVB	4-207
I6HSLES	8-514	I6RO	8-519	KG110S	1-19	KLWVS	4-210
I6KBSI60	8-465	I6SLOS	8-509	KGI60	1-16	KLWVSB	4-208
I6KG60	8-467	I6SLOS	8-499	KGI60S	1-17	KLWVST	4-210
I6KLL110	8-481	I6SLOS	8-471	KL60	4-112	KLWX	4-207
I6KLLABD	8-483	I6SLOS	8-490	KL60	7-410	KLX	4-115
I6KLLAH	8-487	I6TIM	8-515	KLB	4-114	KLZ	4-189
I6KLLAHV	8-487	I6V60.200	8-472	KLBS60	7-409	KLZAH	4-194
I6KLLB	8-484	I6VF60	8-473	KLL110	4-127	KLZAHV	4-194
I6KLLBK	8-490	I6VFCB	8-476	KLL110.6	4-128	KLZB	4-191
I6KLLDK	8-483	I6VFK	8-474	KLL85	4-126	KLZDSH	4-194
I6KLLDSH	8-487	I6VFGK30	8-475	KLLABD	4-129	KLZDSV	4-195
I6KLLDSV	8-488	I6VFKK25	8-475	KLLAH	4-135	KLZKP	4-197
I6KLLI60	8-479	I6VFKS	8-475	KLLAHV	4-135	KLZSB	4-193
I6KLLKP	8-489	I6VFM	8-476	KLLB	4-130	KLZT	4-191
I6KLLSB	8-486	I6VMM	8-477	KLLBK	4-135	KLZVB	4-192
I6KLLT	8-484	I6VFO	8-477	KLLDK	4-129	KLZVS	4-195
I6KLLVB	8-485	I6VM	8-516	KLLDSH	4-136	KLZVSB	4-193
I6KLLVS	8-488	I6VMB	8-477	KLLDSV	4-136	KLZVST	4-195
I6KLLVSB	8-486	I6VOMEGA	8-510	KLLI60	4-124	KLZX	4-192
I6KLLVST	8-488	I6WK	8-513	KLLI60.6	4-125	KPBS	7-408
I6KLLX	8-485	I6WSU	8-513	KLLIBS60	7-434	KPBSKL	7-409
I6KLM	8-491	IDP	6-390	KLLKP	4-138	KPCL	5-256
I6KLMAH	8-495	IOK	6-384	KLLSB	4-134	KPVF	3-87
I6KLMAHV	8-496	K		KLLT	4-131	KPVFL35	3-87
I6KLMB	8-493	KBS110	1-13	KLLVB	4-133	KPW	1-38
I6KLMDSH	8-496	KBS110.6	1-14	KLLVS	4-136	KR	1-26
I6KLMDSV	8-496	KBS35	1-10	KLLVSB	4-134	KUWDT	6-347
I6KLMKP	8-498	KBS60	1-11	L			
I6KLMSB	8-495	KBS60	7-408	KLLVST	4-137	L25	5-269
I6KLMT	8-493	KBS85	1-12	KLLX	4-132	L25.50	5-269
I6KLMVB	8-494	KBSCL60	1-8	KLM	4-173	L50.50	5-269
I6KLMVS	8-497	KBSCL60.6	1-9	KLMAH	4-178	LBS	7-435
I6KLMVS	8-495	KBSI35	1-6	KLMAHV	4-178	LOMEGA150	7-412
I6KLMVST	8-497	KBSI60	1-7	KLMB	4-175	LOMEGACLU150	3-83
I6KLMX	8-494	KBSI60	7-434	KLMDSH	4-178	LOMEGACLU150	5-244
I6KLMZWAB	8-507	KBSM(I)60	1-15	KLMDSV	4-179	LV	1-38
I6KLMZWAB	8-497	KBV	1-38	KLMKP	4-181	LVBS60	7-410
I6KLMZWABD	8-501	KBV	8-472	KLMSB	4-177		
I6KLMZWABD	8-492	KBVCL	1-39	KLMT	4-175	M	
I6KLMZWBK	8-508	KCL	5-246	KLMVB	4-176	M	5-282
I6KLMZWBK	8-498	KCLBS	7-414	KLMVS	4-179	M	7-455
I6KLZ	8-500	KDRKK3	6-370	KLMVSB	4-177	MK	6-392
I6KLZAH	8-505	KDRKK3	6-358	KLMVST	4-179	MP	1-33
I6KLZAHV	8-505	KDRKK3	6-330	KLMX	4-176	MP3.41.41	5-275
I6KLZB	8-502	KDVIRK2	6-367	KLMZWAB	4-211	MP41.21	5-272
I6KLZDSH	8-506	KDVIRK2	6-353	KLMZWAB	4-196	MP41.41	5-273
I6KLZDSV	8-506	KDVIRK2	6-332	KLMZWABD	4-205	MP41.41DG	5-274
I6KLZKP	8-508	KDVIRK3	6-369	KLMZWABD	4-190	MPCL	7-440
I6KLZSB	8-504	KDVIRK3	6-356	KLMZWABD	4-174	MPCL	7-416
I6KLZT	8-502	KDVIRK3	6-335	KLMZWBK	4-180	MPCL41.21	5-257
I6KLZVB	8-503	KDVIT2	6-331	KLMZWBK	4-196	MPV	1-33
I6KLZVS	8-507	KDVIT3	6-333	KLMZWBK	4-211	MPVCL	1-34
I6KLZVS	8-504	KDVIT3	6-334	KLT	4-115	MPVFCL	3-80
I6KLZVST	8-507	KDVITV3	6-343	KLB	4-116		
I6KLZX	8-503	KDVITWD3	6-344	KLW	4-204	N	
I6KPFV	8-474	KDVITWDV3	6-344	KLWAH	4-209	NATO15	1-20
I6LOMEGA150	8-512	KDVIZ	6-385	KLWAHV	4-209	NEO	6-320
I6M	8-518	KDVKK2	6-352	KLWB	4-206	NEOAVT	6-382
I6MP41.21	8-514	KDVKK2	6-326	KLWDSH	4-209	NEOT	6-382
I6MP41.41	8-515	KDVKK3	6-368	KLWDSV	4-210	NEOTVT	6-382
I6PB	8-509	KDVKK3	6-368	KLWKP	4-212		

Alphabetical list of references

Reference	Page	Reference	Page	Reference	Page
O		TFCL60	2-52	VH	1-23
OBG	5-230	TFCL60S	2-53	VK	6-319
OBG	3-78	TFCL85	2-54	VM	5-282
OBGVF	3-78	TFCL85S	2-55	VM	7-456
OBZ130	5-240	TIM	5-278	VM6334	5-279
OBZ180	5-241	TIM	7-442	VM6334	7-455
OHE	6-384	TIM	7-418	VMB	5-240
OV	6-392	TSBL	6-391	VMB	3-84
OVG	6-362	TSBU	6-386	VMK	5-282
OVGAN	6-372	TSBU45	6-386	VMK	7-456
OVGB	6-364	TSBU50	6-387	VOMEGA	5-244
OVGBP	6-362	TSBUD	6-387	VOMEGA	7-413
OVGE	6-365	U		VS	1-32
OVGEQ	6-373	U24	5-271	VS41.41.62	5-276
OVGEQH	6-373	U48	5-271	VSB	6-318
OVGHV	6-373	V		VSZ	5-284
OVGK	6-365	V110.200	1-37	W	
OVGP	6-371	V15.200	1-35	WKCL	5-250
OVGT	6-364	V35	1-35	WKMP41.21	5-250
OVGTAP	6-372	V35.200	1-36	WKMP41.41	5-251
OVGTR	6-371	V35.200	2-60	WKMPCL41.21	5-251
OVGVST	6-372	V35.200	3-87	WKMPCL41.41	5-252
OVGZ	6-371	V60	1-36	WKS	5-247
P		V60.200	1-37	WKSS	5-248
PBR	5-229	V60.200	4-117	WKUMP41.41	5-252
Q		V60.200	2-61	WKUMPCL41.41	5-253
QL	7-435	V85	1-36	WSUN	5-245
R		V85.200	1-37	Z	
RB	5-283	V85.200	2-61	Z25	5-270
RBK	5-281	VB90	1-28	Z50	5-270
RBKBSM	1-33	VBCL	1-29	ZCL	3-80
RBS	5-285	VE	6-319		
RM	5-283	VERP	6-322		
RO	5-284	VERV	6-321		
RO	7-457	VEVP	6-322		
ROTD	5-284	VEVV	6-321		
S		VFCB	5-230		
SB90	1-27	VFCB	3-77		
SBCL	1-27	VFCL	3-77		
SDB	1-30	VFK	3-85		
SDBG	5-229	VFKG30	3-85		
SKL60	4-113	VFKK25	3-86		
SKPD	5-275	VFKNIP	3-88		
SKPE	5-275	VFKS	3-86		
SLIS	1-34	VFM	3-76		
SLOS	1-34	VFMM	3-76		
SLOS	3-84	VFMM	3-76		
SLOS	4-117	VFO	3-75		
SLOS	4-166	VFOCL	3-75		
SLOS	4-152	VFSLOSCL	3-85		
SLOS	4-138	VFU110	3-73		
SLOS	4-212	VFU35	3-70		
SLOS	4-197	VFU60	3-71		
SLOS	4-181	VFU85	3-72		
SLOS	6-374	VFUL35	3-68		
SSBU	6-389	VFUL60	3-69		
SYBS	7-411	VFVLB	3-79		
T		VGI28	6-315		
T	1-24	VGI38	6-316		
TFCL110	2-56	VGI48	6-316		
TFCL110S	2-57	VGLI28	6-317		
		VGLI38	6-317		
		VGLI48	6-318		