



ELECTRICAL CONTINUITY DECLARATION

Producer:	VERGOKAN NV	
Reportname:	KBSCL60	
Product description:	Cable tray clickable	
Devicesunder test :	KBSCL60.075.075	
(Productreferences)	KBSCL60.200.075	
	KBSCL60.300.100	
	KBSCL60.400.100	
	VM6.10	
	KBVCL	
Test according to:	§ 11.1.2 of the IEC 61537	
Description of testmethode:	scription of testmethode: A current of 25 A \pm 1A A.C. having a frequency of 50 Hz to 60 H supplied by a source with a no-load voltage not exceeding 12 V shall be passed hrough the length of the samples. The voltage of shall be measured between two points 50 mm each side of the coupler or integral coupling and again between two points 500 n apart on one side of the joint. The impedances shall not exceed m Ω across the joint and 5 m Ω per meter without the joint.	
Manufactured by:	VERGOKAN N.V.	
Test device:	HYAMP III 3130	
Calibration certificate number:	130624-3130_9352036	
3		

[Declaration]:

We declare that above mentioned products are tested by VERGOKAN according to § 11.1.2 of the IEC 61537.







DESCRIPTION OF TEST:

Test number	Setup	Measuring points	Criteria to pass the test
1	Two cable trays KBSCL60.075.075 coupled with click only	On both trays 50mm of the coupling.	Impedance can not exceed 50mΩ
2	Two cable trays KBSCL60.200.075 coupled with click only	On both trays 50mm of the coupling.	Impedance can not exceed 50mΩ
3	Two cable trays KBSCL60.300.100 coupled with click only	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
4	Two cable trays KBSCL60.400.100 coupled with click only	On both trays 50mm of the coupling.	Impedance can not exceed 50mΩ
5	Two cable trays KBSCL60.075.075 coupled with VM6.10	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
6	Two cable trays KBSCL60.200.075 coupled with VM6.10	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
7	Two cable trays KBSCL60.300.100 coupled with VM6.10	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
8	Two cable trays KBSCL60.400.100 coupled with VM6.10	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
9	Two cable trays KBSCL60.075.075 coupled with KBVCL	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
10	Two cable trays KBSCL60.200.075 coupled with KBVCL	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
. 11	Two cable trays KBSCL60.300.100 coupled with KBVCL	On both tray's 50mm of the coupling.	Impedance can not exceed 50mΩ
12	Two cable trays KBSCL60.400.100 coupled with KBVCL	On both tray's 50mm of the coupling.	Impedance can not exceed $50m\Omega$
13	KBSCL60.075.075	On the tray, 500mm apart from each other	Impedance can not exceed 5mΩ/m
14	KBSCL60.200.100	On the tray, 500mm apart from each other	Impedance can not exceed 5mΩ/m
15	KBSCL60.300.100	On the tray, 500mm apart from each other	Impedance can not exceed 5mΩ/m
16	KBSCL60.400.100	On the tray, 500mm apart from each other	Impedance can not exceed 5mΩ/m

RESULTS OF TEST:

Georges Xhauflaire Inspector

INSPECTORS BENELUX

RF 7.3.9, Rev 1, dd 18.10.13





Test number	Test	Impedance	Result			
	1	4 mΩ	Pass			
1	2	3 mΩ	Pass			
	3	3 mΩ	Pass			
	1	2 mΩ	Pass			
2	2	2 mΩ	Pass			
	3	2 mΩ	Pass			
	1	2 mΩ	Pass			
3	2	2 mΩ	Pass			
	3	2 mΩ	Pass			
	1	4 mΩ	Pass			
4	2	4 mΩ	Pass			
	3	4 mΩ	Pass			
	1	2 mΩ	Pass			
5	2	2 mΩ	Pass			
	3	2 mΩ	Pass			
	1	2 mΩ	Pass			
6	2	2 mΩ	Pass			
	3	2 mΩ	Pass			
	1	2 mΩ	Pass			
7	2	2 mΩ	Pass			
		2 mΩ	Pass			
	3 1	4 mΩ	Pass			
8	2	4 mΩ	Pass			
	3	3 mΩ	Pass			
	1	7 mΩ	Pass			
9	2	7 mΩ	Pass			
	3	7 mΩ	Pass			
	1	2 mΩ	Pass			
10	2	2 mΩ	Pass			
	3	2 mΩ	Pass			
11	1	5 mΩ	Pass			
	2	5 mΩ	Pass			
	3	5 mΩ	Pass			
12	1	5 mΩ	Pass			
	2	6 mΩ	Pass			
	3	5 mΩ	Pass			
	1	2 mΩ	Pass			
13	2	2 mΩ	Pass			
	3	2 mΩ	Pass			
	1	2 mΩ	Pass			
14		2 mΩ	Pass			
	3	2 mΩ	Pass			
15	1	2 mΩ	Pass			
	2	2 mΩ	Pass			
	3	2 mΩ	Pass			
16	1	2 mΩ	Pass			
	2	2 mΩ	Pass			
	3	2 mΩ	Pass			







CONCLUSION:

All the devices under test where tested as described above and did meet their criteria to pass the test. We can state that the cable tray KBSCL60.---- is conform to § 11.1.2 of the IEC 61537.

Oudenaarde, 12/06/2019

Meerbloem Melden 16
9700 Oudenaarde
VAT BE 0422 878 131
Reg Oud 26 920
Reg Oud 26 920

Gino Declercq Operations Director

On condition that the product(s) is/are used in the manner intended and/or in accordance with the current installation standards and/or with the manufacturer's recommendations.

Georges Xhauflaire Inspector