



ZCL

Z-Support klipsbar



| | Max. Belastung (in daN) |
|--------|-------------------------|
| ZCL100 | 150 |
| ZCL150 | 150 |
| ZCL200 | 120 |
| ZCL300 | 105 |
| ZCL400 | 90 |
| ZCL500 | 80 |
| ZCL600 | 65 |

| Referenz | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Einheit |
|---------------|---------|---------|------------|---------|--------|----|---------|
| ZCL100 | 14 | 60 | | 180 | 0,135 | 12 | STK |
| ZCL150 | 14 | 60 | | 230 | 0,165 | 12 | STK |
| ZCL200 | 14 | 60 | | 280 | 0,210 | 12 | STK |
| ZCL300 | 14 | 60 | | 380 | 0,265 | 12 | STK |
| ZCL400 | 14 | 60 | | 480 | 0,315 | 12 | STK |
| ZCL500 | 14 | 60 | | 580 | 0,365 | 12 | STK |
| ZCL600 | 14 | 60 | | 680 | 0,415 | 12 | STK |

Zu befestigen mit Gewindestange TIM6 oder TIM8.

Max. Belastung (in daN): Gleichmäßig verteilte Last über die gesamte Breite des Auslegers.

Gewindestange separat zu bestellen.