


KLM125VB

Fallstück für KLM125



Zu befestigen mit:



Verzahnte
Flanshmutter
(DIN 6923)
RM

Selbstsichernde
Schraube (DIN
603)
RBK

Radius: 600 mm

Referenz	Oberfläche	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Einheit
KLM125VB150	SZ	125	158			4,974	1	STK
KLM125VB200	SZ	125	208			5,089	1	STK
KLM125VB300	SZ	125	308			5,320	1	STK
KLM125VB400	SZ	125	408			5,550	1	STK
KLM125VB450	SZ	125	458			5,666	1	STK
KLM125VB500	SZ	125	508			5,781	1	STK
KLM125VB600	SZ	125	608			6,011	1	STK
KLM125VB750	SZ	125	758			6,357	1	STK
KLM125VB800	SZ	125	808			6,472	1	STK
KLM125VB900	SZ	125	908			6,702	1	STK
KLM125VB1000	SZ	125	1008			6,933	1	STK
ZMKLM125VB150	DF	125	158			4,974	1	STK
ZMKLM125VB200	DF	125	208			5,089	1	STK
ZMKLM125VB300	DF	125	308			5,320	1	STK
ZMKLM125VB400	DF	125	408			5,550	1	STK
ZMKLM125VB450	DF	125	458			5,666	1	STK
ZMKLM125VB500	DF	125	508			5,781	1	STK
ZMKLM125VB600	DF	125	608			6,011	1	STK
ZMKLM125VB750	DF	125	758			6,357	1	STK
ZMKLM125VB800	DF	125	808			6,472	1	STK
ZMKLM125VB900	DF	125	908			6,702	1	STK
ZMKLM125VB1000	DF	125	1008			6,933	1	STK

Min. Anzahl Schrauben und Muttern: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender