


KLWSB

Steigestück für KLW



Zu befestigen mit:



Selbstsichernde
Schraube (DIN
603)
RBK

Verzahnte
Flanschmutter
(DIN 6923)
RM

Radius: 600 mm

| Referenz | Oberfläche | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Einheit |
|-------------------|------------|---------|---------|------------|---------|--------|---|---------|
| KLWSB200 | SZ | 200 | 208 | | | 7,921 | 1 | STK |
| KLWSB300 | SZ | 200 | 308 | | | 8,228 | 1 | STK |
| KLWSB400 | SZ | 200 | 408 | | | 8,535 | 1 | STK |
| KLWSB500 | SZ | 200 | 508 | | | 8,842 | 1 | STK |
| KLWSB600 | SZ | 200 | 608 | | | 9,149 | 1 | STK |
| ZMKLWSB200 | DF | 200 | 208 | | | 7,921 | 1 | STK |
| ZMKLWSB300 | DF | 200 | 308 | | | 8,228 | 1 | STK |
| ZMKLWSB400 | DF | 200 | 408 | | | 8,535 | 1 | STK |
| ZMKLWSB500 | DF | 200 | 508 | | | 8,842 | 1 | STK |
| ZMKLWSB600 | DF | 200 | 608 | | | 9,149 | 1 | STK |

Min. Anzahl Schrauben und Muttern: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender