


KLWVB

Fallstück für KLW



Zu befestigen mit:



Verzahnte
Flanschmutter
(DIN 6923)
RM

Selbstsichernde
Schraube (DIN
603)
RBK

Radius: 600 mm

| Referenz | Oberfläche | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Einheit |
|-------------------|------------|---------|---------|------------|---------|--------|---|---------|
| KLWVB200 | SZ | 200 | 208 | | | 7,795 | 1 | STK |
| KLWVB300 | SZ | 200 | 308 | | | 8,026 | 1 | STK |
| KLWVB400 | SZ | 200 | 408 | | | 8,256 | 1 | STK |
| KLWVB500 | SZ | 200 | 508 | | | 8,487 | 1 | STK |
| KLWVB600 | SZ | 200 | 608 | | | 8,717 | 1 | STK |
| ZMKLWVB200 | DF | 200 | 208 | | | 7,795 | 1 | STK |
| ZMKLWVB300 | DF | 200 | 308 | | | 8,026 | 1 | STK |
| ZMKLWVB400 | DF | 200 | 408 | | | 8,256 | 1 | STK |
| ZMKLWVB500 | DF | 200 | 508 | | | 8,487 | 1 | STK |
| ZMKLWVB600 | DF | 200 | 608 | | | 8,717 | 1 | STK |

Min. Anzahl Schrauben und Muttern: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender