


KLZSB

Steigestück für KLZ



Zu befestigen mit:



Selbstsichernde
Schraube (DIN
603)
RBK

Verzahnte
Flanschmutter
(DIN 6923)
RM

Radius: 600 mm

Referenz	Oberfläche	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Einheit
KLZSB150	SZ	150	150			5,940	1	STK
KLZSB200	SZ	150	208			6,093	1	STK
KLZSB300	SZ	150	308			6,400	1	STK
KLZSB400	SZ	150	408			6,707	1	STK
KLZSB500	SZ	150	508			7,015	1	STK
KLZSB600	SZ	150	608			7,322	1	STK
KLZSB800	-	150	800			7,937	1	STK
KLZSB1000	-	150	1000			8,552	1	STK
ZMKLZSB150	DF		150			5,940	1	STK
ZMKLZSB200	DF	150	208			6,093	1	STK
ZMKLZSB300	DF	150	308			6,400	1	STK
ZMKLZSB400	DF	150	408			6,707	1	STK
ZMKLZSB450	DF	150	450			6,862	1	STK
ZMKLZSB500	DF	150	508			7,015	1	STK
ZMKLZSB600	DF	150	608			7,322	1	STK
ZMKLZSB800	-		800			7,937	1	STK
ZMKLZSB1000	-		1000			8,552	1	STK
PEKLZSB150	-	150	150			5,940	1	STK
PEKLZSB800	-	150	800			7,937	1	STK
PEKLZSB1000	-	150	1000			8,552	1	STK

Min. Anzahl Schrauben und Muttern: 8 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender