

KLZT

T-Stück für KLZ



Zu befestigen mit:



Selbstsichernde
Schraube (DIN
603)
RBK

Verzahnte
Flanschmutter
(DIN 6923)
RM

Radius: 600 mm

	200	300	400	500	600
A	1962	2062	2162	2262	2362

Referenz	Oberfläche	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Einheit
KLZT150	-	150	150			14,299	1	STK
KLZT200	SZ	150	208			14,515	1	STK
KLZT300	SZ	150	308			15,766	1	STK
KLZT400	SZ	150	408			16,892	1	STK
KLZT500	SZ	150	508			18,017	1	STK
KLZT600	SZ	150	608			20,921	1	STK
KLZT800	-	150	800			23,432	1	STK
KLZT1000	-	150	1000			26,680	1	STK
ZMKLZT150	-		150			14,299	1	STK
ZMKLZT200	DF	150	208			14,515	1	STK
ZMKLZT300	DF	150	308			15,766	1	STK
ZMKLZT400	DF	150	408			16,892	1	STK
ZMKLZT500	DF	150	508			18,017	1	STK
ZMKLZT600	DF	150	608			20,921	1	STK
ZMKLZT800	-		800			23,432	1	STK
ZMKLZT1000	-		1000			26,680	1	STK
PEKLZT150	-	150	150			14,299	1	STK
PEKLZT800	-	150	800			23,432	1	STK
PEKLZT1000	-	150	1000			26,680	1	STK

Min. Anzahl Schrauben und Muttern: 12 Stück.

Legenden Oberfläche

- SZ = Sendzimir
- DF = Defender