

Shelter
Flat Pack to Shelter



HD	Referenz	 mm	 mm	 mm	 mm	kg/stk		Lager	Einheit
-	FP2S.1.1500	1500	1500		750	35,733	4	X	STK
-	FP2S.1.1500.S	1500	1500		750	35,733	1	X	STK
-	FP2S.2.1500	1500	1500		1500	62,303	4	X	STK
-	FP2S.2.1500.S	1500	1500		1500	62,303	1	X	STK
-	FP2S.W.1500	1500	1500		490	32,510	4	X	STK
-	FP2S.W.1500.S	1500	1500		490	32,510	1	X	STK

- CHARAKTERISTIK**
- Modulare Bauweise
 - Aufbauzeit vom Flat Pack bis zur Montage unter 7 Minuten.
 - Optimalem Preis-/Leistungsverhältnis
 - Das Dach ist aus hochwertigem Zink-Magnesium
 - Die Konstruktion besteht aus Atkore Unistrut-Profilen
 - Abgabe nur in vollen Verpackungseinheiten.

- TECHNISCHE AUSKÜNFTE**
- Kombination von Feuerverzinkung und Zink-Magnesium teilen
 - keine Ausführung Option möglich

FP2S PV-Shelter
Installation Guide



