


## **I6KBSCL60**Cable Tray Clickable





I	1,5	2,0	2,5	3,0	
KBSCL60060	64,4	46,5	30,4	23,5	•
KBSCL60.(75-300).075	121,9	81,1	54,0	33,7	
KBSCL60.(400).075		63,6	41,6	33,1	
KBSCL60.(75-400).100	149,9	99,3	63,9	46,1	
KBSCL60.(500-600).100	113,7	76,1	55,8	43,9	

Clicking ends Alternative perforations Return flanges

Reference	† mm	↔ mm	→  ← mm	<b>≠</b> mm	kg/m	$\Diamond$	Unit
I6KBSCL60.100.080	60	100	0,80	3000	1,396	3	М
I6KBSCL60.200.080	60	200	0,80	3000	2,005	3	М
I6KBSCL60.300.080	60	300	0,80	3000	2,600	3	М
I6KBSCL60.400.080	60	400	0,80	3000	3,231	3	М

## **LOAD DIAGRAM**

This diagram illustrates the permissible uniformly distributed loads applied to multiple supports. They comply with IEC 61537 with connection in the centre of the span and the end span =  $0.8 \times 10^{-2}$  x the span.

F = max. admissible load (daN/m)

L =support distance (m) Max. deflection (m) = L/100

## **FEATURES**

- Clickable.
- The simplest jointing system, with a single movement.
- Rapid Just click and ready for the next joint. Immediate alignment at the same time.
- Strong As strong as a bolted joint.
- Reliable Maximum load with snap-fit joint. Multiple jointing options available.
- Cost-effective Working faster results in immediate time and cost savings.
- High standard Wide and complete range of accessories available.

Etched perforations for:

- better stability
- extra load-bearing capacity
- better cooling

Longitudinal and transverse perforations for:

- better fixing to the support
- convenient cable bundling

Additional equipotential bonding available by 1. snap-fit joint, 2. bolted joint and 3. push-through lip in the bottom.

## **TECHNICAL INFORMATION**

Perforation pattern varies according to width.

Transverse perforation as from 200 mm width.

16 mm dia. and 20.4 mm dia. openings to be provided for fitting a gland. SLIS60 snap-in partition to suit width as from 75 mm every 50 mm in the width direction.

Can be secured with I6VM6.10 or KBVCL as an option.



