

# I6KLM125VSB

## Flexible (rising / low) bend for I6KLM125



**Fix with:**



Round head  
square neck bolt  
(DIN 603)  
I6RBK

Nut (DIN 934)  
I6M



Giant washer  
(DIN 125-1 A)  
I6RO

Reference	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unit
<b>I6KLM125VSB150</b>	125	150			10,337	1	STK
<b>I6KLM125VSB200</b>	125	218		1135	10,455	1	STK
<b>I6KLM125VSB300</b>	125	318		1135	10,692	1	STK
<b>I6KLM125VSB400</b>	125	418		1135	10,928	1	STK
<b>I6KLM125VSB450</b>	125	450			11,046	1	STK
<b>I6KLM125VSB500</b>	125	518		1135	11,164	1	STK
<b>I6KLM125VSB600</b>	125	618		1135	11,400	1	STK
<b>I6KLM125VSB750</b>	125	750			11,636	1	STK
<b>I6KLM125VSB800</b>	125	800			11,873	1	STK
<b>I6KLM125VSB900</b>	125	900			12,109	1	STK
<b>I6KLM125VSB1000</b>	125	1000			12,346	1	STK

Minimum number bolts and nuts: 8 pieces.

Pickled and passivated.