



KLL110.6

Cable ladder



Fix with:



Toothed round
head bolt / flange
nut

Joiner for KLL
KLLKP

VM

Side walls: perforated S-profile

Perforated C rungs 15x30

Standard finish	Pre-galvanised
Optional finish	Hot-dip galvanised
Optional finish	Coating

HD	Reference	↑ mm	↔ mm	≡ mm	↔ mm	kg /m	📦	Stock	Unit
HD	KLL110.200.6	110	200		6000	3,699	36		M
HD	KLL110.300.6	110	300		6000	3,937	36		M
HD	KLL110.400.6	110	400		6000	4,174	36		M
HD	KLL110.500.6	110	500		6000	4,412	36		M
HD	KLL110.600.6	110	600		6000	4,65	36		M

LOAD DIAGRAM

This diagram illustrates the permissible uniformly distributed horizontal loads applied to multiple supports. They comply with IEC 61537 with connection in the centre of the span and the end span = 0,8x the span.

F = max. admissible load (daN/m)

L = support distance (m)

Max. deflection (m) = L/100

CHARACTERISTICS

- lightweight
- strong
- partition (SLOS85) can be fixed to the cable ladder with a sliding nut (GM6) and pan head bolt (RB6.10)
- no further coupling holes are required if the cable ladder is cut.
- rungs are perforated to enable efficient attachment of cables.