


KLLT

T-piece for KLL



Radius: 300 mm

| | | | | | | |
|---|------|------|------|------|------|------|
| | 150 | 200 | 300 | 400 | 500 | 600 |
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

Fix with:



Toothed round head bolt / flange nut
VM

| Reference | Finish | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|----------------------|--------|---------|---------|------------|---------|--------|---|------|
| KLLT60.150 | - | 60 | 141 | | | 2,229 | 1 | STK |
| KLLT60.200 | - | 60 | 191 | | | 2,821 | 1 | STK |
| KLLT60.300 | - | 60 | 291 | | | 3,447 | 1 | STK |
| KLLT60.400 | - | 60 | 391 | | | 3,882 | 1 | STK |
| KLLT60.450 | - | 60 | 443 | | | 4,099 | 1 | STK |
| KLLT60.500 | - | 60 | 491 | | | 4,317 | 1 | STK |
| KLLT60.600 | - | 60 | 591 | | | 4,753 | 1 | STK |
| KLLT60.750 | SZ | 60 | 750 | 1,25 | | 7,554 | 1 | STK |
| KLLT60.800 | SZ | 60 | 800 | 1,25 | | 7,896 | 1 | STK |
| KLLT60.900 | SZ | 60 | 900 | 1,25 | | 8,580 | 1 | STK |
| KLLT110.150 | - | 110 | 145 | | | 3,635 | 1 | STK |
| KLLT110.200 | - | 110 | 195 | | | 4,131 | 1 | STK |
| KLLT110.300 | - | 110 | 295 | | | 4,806 | 1 | STK |
| KLLT110.400 | - | 110 | 395 | | | 5,290 | 1 | STK |
| KLLT110.450 | - | 110 | 445 | | | 5,533 | 1 | STK |
| KLLT110.500 | - | 110 | 495 | | | 5,775 | 1 | STK |
| KLLT110.600 | - | 110 | 595 | | | 6,260 | 1 | STK |
| KLLT110.750 | - | 110 | 750 | | | 6,987 | 1 | STK |
| KLLT110.800 | SZ | 110 | 800 | 1,25 | | 9,478 | 1 | STK |
| KLLT110.900 | - | 110 | 900 | | | 7,714 | 1 | STK |
| ZMKLLT60.150 | DF | 60 | 150 | 1,25 | | 3,229 | 1 | STK |
| ZMKLLT60.200 | DF | 60 | 200 | 1,25 | | 3,483 | 1 | STK |
| ZMKLLT60.300 | DF | 60 | 300 | 1,25 | | 4,154 | 1 | STK |
| ZMKLLT60.400 | DF | 60 | 400 | 1,25 | | 4,721 | 1 | STK |
| ZMKLLT60.450 | DF | 60 | 450 | 1,25 | | 5,005 | 1 | STK |
| ZMKLLT60.500 | DF | 60 | 500 | 1,25 | | 5,566 | 1 | STK |
| ZMKLLT60.600 | DF | 60 | 600 | 1,25 | | 6,193 | 1 | STK |
| ZMKLLT60.750 | DF | 60 | 750 | 1,25 | | 7,554 | 1 | STK |
| ZMKLLT60.800 | DF | 60 | 800 | 1,25 | | 7,896 | 1 | STK |
| ZMKLLT60.900 | DF | 60 | 900 | 1,25 | | 8,580 | 1 | STK |
| ZMKLLT110.150 | DF | 110 | 150 | 1,25 | | 4,493 | 1 | STK |
| ZMKLLT110.200 | DF | 110 | 200 | 1,25 | | 4,772 | 1 | STK |
| ZMKLLT110.300 | DF | 110 | 300 | 1,25 | | 5,491 | 1 | STK |
| ZMKLLT110.400 | DF | 110 | 400 | 1,25 | | 6,107 | 1 | STK |
| ZMKLLT110.450 | DF | 110 | 450 | 1,25 | | 6,416 | 1 | STK |
| ZMKLLT110.500 | DF | 110 | 500 | 1,25 | | 7,001 | 1 | STK |
| ZMKLLT110.600 | DF | 110 | 600 | 1,25 | | 7,677 | 1 | STK |
| ZMKLLT110.750 | DF | 110 | 750 | 1,25 | | 9,111 | 1 | STK |
| ZMKLLT110.800 | DF | 110 | 800 | 1,25 | | 9,478 | 1 | STK |
| ZMKLLT110.900 | DF | 110 | 900 | 1,25 | | 10,210 | 1 | STK |

Minimum number bolts and nuts VM6.10: 12 pieces.



Legend finish
- SZ = Sendzimir
- DF = Defender