

KLLVB.45

External riser 45° for KLL



Radius: 300 mm

Standard finish


Pre-galvanised

Optional finish

Hot-dip galvanised

HD	Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit
HD	KLLVB60.150.45	60	143			1,146	1		STK
HD	KLLVB60.200.45	60	193			1,222	1		STK
HD	KLLVB60.300.45	60	293			1,373	1		STK
HD	KLLVB60.400.45	60	393			1,524	1		STK
HD	KLLVB60.450.45	60	443			1,600	1		STK
HD	KLLVB60.500.45	60	493			1,676	1		STK
HD	KLLVB60.600.45	60	593			1,826	1		STK
HD	KLLVB110.150.45	110	145			2,201	1		STK
HD	KLLVB110.200.45	110	195			2,066	1		STK
HD	KLLVB110.300.45	110	295			2,217	1		STK
HD	KLLVB110.400.45	110	395			2,369	1		STK
HD	KLLVB110.450.45	110	445			2,444	1		STK
HD	KLLVB110.500.45	110	495			2,520	1		STK
HD	KLLVB110.600.45	110	595			2,671	1		STK

Fix with:



Toothed round head bolt / flange nut
VM

Minimum number bolts and nuts VM6.10: 8 pieces.