


KBWW

Cable ladder 200 with floor plate





Fix with:





Joiner for KLW **KLWKP**

Round head square neck bolt (DIN 603) **RBK**



Flange nut (DIN 6923) RM

Cable ladder for large support distances up to 9 metres Perforated C datarungs 41x21 With floor plate

Usable inner height: 177 mm Rung distance: 300 mm

rang distance. 500 mm							
Reference	‡ mm	↔ mm	→ ← mm	⇒ mm	kg/m	\Diamond	Unit
Reference					J .	•	Offic
KBWW200	200	200		6000	10,986	6	М
KBWW300	200	300		6000	11,942	6	М
KBWW400	200	400		6000	12,899	6	М
KBWW500	200	500		6000	13,855	6	М
KBWW600	200	600		6000	14,811	6	M

LOAD DIAGRAM

Graph valid for KLW. This diagram illustrates the permissible uniformly distributed horizontal loads applied to multiple supports. They comply with IEC 61537

F = max. admissible load (daN/m)

L = support distance (m) Max. deflection (m) = L/200

CHARACTERISTICS

- strong
- useable inner height 177 mm, ideal for large diameter cables
- no further coupling holes are required if the cable ladder is cut
- no joiners are required to attach accessories such as bends, tees etc.
- rungs are perforated to enable efficient attachment of cables
- partition (SLOS110) can be fixed to the cable ladder with a sliding nut (PNP06) and pan head bolt (RB6.20).

TECHNICAL INFORMATION

- Side walls are constructed from S profile with a return flange and are continuously perforated
- C-profile rungs are fixed at 300 mm intervals.
- rungs are mechanically attached to the side wall of the cable ladder.
- rungs are alternately placed with openings upwards and downwards.