


## VB90


### Low elbow 90°



#### Fix with:



Toothed round  
head bolt / flange  
nut  
VM



Round head  
square neck bolt  
/ flange nut  
VMK

Slides over the cable trays

Radius: 100 mm

To order: Height 35 mm - 85 mm - 110 mm (only in SZ et HD)

Standard finish

Pre-galvanised

Optional finish

| HD | Reference            | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Stock | Unit |
|----|----------------------|---------|---------|------------|---------|--------|---|-------|------|
| -  | <b>VB90.60.050</b>   | 60      | 50      |            |         | 0,550  | 1 | X     | STK  |
| -  | <b>VB90.60.075</b>   | 60      | 75      |            |         | 0,630  | 1 | X     | STK  |
| -  | <b>VB90.60.100</b>   | 60      | 100     |            |         | 0,650  | 1 | X     | STK  |
| -  | <b>VB90.60.150</b>   | 60      | 150     |            |         | 0,780  | 1 | X     | STK  |
| -  | <b>VB90.60.200</b>   | 60      | 200     |            |         | 0,850  | 1 | X     | STK  |
| -  | <b>VB90.60.300</b>   | 60      | 300     |            |         | 1,080  | 1 | X     | STK  |
| -  | <b>VB90.60.400</b>   | 60      | 400     |            |         | 1,330  | 1 | X     | STK  |
| -  | <b>VB90.60.500</b>   | 60      | 500     |            |         | 1,430  | 1 | X     | STK  |
| -  | <b>VB90.60.600</b>   | 60      | 600     |            |         | 1,600  | 1 | X     | STK  |
| -  | <b>ZMVB90.60.050</b> | 60      | 50      |            |         | 0,55   | 1 |       | STK  |
| -  | <b>ZMVB90.60.075</b> | 60      | 75      |            |         | 0,63   | 1 |       | STK  |
| -  | <b>ZMVB90.60.100</b> | 60      | 100     |            |         | 0,65   | 1 |       | STK  |
| -  | <b>ZMVB90.60.150</b> | 60      | 150     |            |         | 0,78   | 1 |       | STK  |
| -  | <b>ZMVB90.60.200</b> | 60      | 200     |            |         | 0,85   | 1 |       | STK  |
| -  | <b>ZMVB90.60.300</b> | 60      | 300     |            |         | 1,08   | 1 |       | STK  |
| -  | <b>ZMVB90.60.400</b> | 60      | 400     |            |         | 1,33   | 1 |       | STK  |
| -  | <b>ZMVB90.60.500</b> | 60      | 500     |            |         | 1,43   | 1 |       | STK  |
| -  | <b>ZMVB90.60.600</b> | 60      | 600     |            |         | 1,6    | 1 |       | STK  |

Minimum number bolts and nuts: 8 pieces.