


KLLB.45

Horizontal bend 45° for KLL

Radius: 300 mm



Fix with:



Toothed round head bolt / flange nut
VM

Reference	Finish	↕ mm	↔ mm	→ ← mm	↔↔ mm	kg/stk	📦	Unit
KLLB60.150.45	-	60	143			1,244	1	STK
KLLB60.200.45	-	60	193			1,424	1	STK
KLLB60.300.45	-	60	293			1,781	1	STK
KLLB60.400.45	-	60	393			2,139	1	STK
KLLB60.450.45	-	60	443			2,318	1	STK
KLLB60.500.45	-	60	493			2,497	1	STK
KLLB60.600.45	-	60	593			2,855	1	STK
KLLB60.750.45	SZ	60	750	1,25		2,842	1	STK
KLLB60.900.45	SZ	60	900	1,25		3,283	1	STK
KLLB60.800.45	SZ	60	800	1,25		2,989	1	STK
KLLB110.150.45	-	110	145			2,299	1	STK
KLLB110.200.45	-	110	195			2,120	1	STK
KLLB110.300.45	-	110	295			2,538	1	STK
KLLB110.400.45	-	110	395			2,955	1	STK
KLLB110.450.45	-	110	445			3,164	1	STK
KLLB110.500.45	-	110	495			3,374	1	STK
KLLB110.600.45	-	110	595			3,791	1	STK
KLLB110.750.45	-	110	750			4,418	1	STK
KLLB110.800.45	SZ	110	800	1,25		3,810	1	STK
KLLB110.900.45	-	110	900			5,045	1	STK
ZMKLLB60.150.45	DF	60	150	1,25		1,075	1	STK
ZMKLLB60.200.45	DF	60	200	1,25		1,223	1	STK
ZMKLLB60.300.45	DF	60	300	1,25		1,517	1	STK
ZMKLLB60.400.45	DF	60	400	1,25		1,811	1	STK
ZMKLLB60.450.45	DF	60	450	1,25		1,958	1	STK
ZMKLLB60.500.45	DF	60	500	1,25		2,106	1	STK
ZMKLLB60.600.45	DF	60	600	1,25		2,400	1	STK
ZMKLLB60.750.45	DF	60	750	1,25		2,842	1	STK
ZMKLLB60.800.45	DF	60	800	1,25		2,989	1	STK
ZMKLLB60.900.45	DF	60	900	1,25		3,283	1	STK
ZMKLLB110.150.45	DF	110	150	1,25		1,647	1	STK
ZMKLLB110.200.45	DF	110	200	1,25		1,814	1	STK
ZMKLLB110.300.45	DF	110	300	1,25		2,147	1	STK
ZMKLLB110.400.45	DF	110	400	1,25		2,479	1	STK
ZMKLLB110.450.45	DF	110	450	1,25		2,646	1	STK
ZMKLLB110.500.45	DF	110	500	1,25		2,812	1	STK
ZMKLLB110.600.45	DF	110	600	1,25		3,145	1	STK
ZMKLLB110.750.45	DF	110	750	1,25		3,644	1	STK
ZMKLLB110.900.45	DF	110	900	1,25		4,143	1	STK
ZMKLLB110.800.45	DF	110	800	1,25		3,810	1	STK

Minimum number bolts and nuts VM6.10: 8 pieces.

Legend finish

- SZ = Sendzimir
- DF = Defender