


## KLLSB.45

### Internal riser 45° for KLL

Radius: 300 mm



Fix with:



Toothed round head bolt / flange nut  
VM

| Reference         | Finish | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔↔<br>mm | kg/stk | 📦 | Unit |
|-------------------|--------|---------|---------|------------|----------|--------|---|------|
| KLLSB60.150.45    | -      | 60      | 143     |            |          | 1,146  | 1 | STK  |
| KLLSB60.200.45    | -      | 60      | 193     |            |          | 1,222  | 1 | STK  |
| KLLSB60.300.45    | -      | 60      | 293     |            |          | 1,373  | 1 | STK  |
| KLLSB60.400.45    | -      | 60      | 393     |            |          | 1,524  | 1 | STK  |
| KLLSB60.450.45    | -      | 60      | 443     |            |          | 1,600  | 1 | STK  |
| KLLSB60.500.45    | -      | 60      | 493     |            |          | 1,676  | 1 | STK  |
| KLLSB60.600.45    | -      | 60      | 593     |            |          | 1,826  | 1 | STK  |
| KLLSB60.750.45    | SZ     | 60      | 750     | 1,25       |          | 2,147  | 1 | STK  |
| KLLSB60.800.45    | SZ     | 60      | 800     | 1,25       |          | 2,234  | 1 | STK  |
| KLLSB60.900.45    | SZ     | 60      | 900     | 1,25       |          | 2,409  | 1 | STK  |
| KLLSB110.150.45   | -      | 110     | 145     |            |          | 2,201  | 1 | STK  |
| KLLSB110.200.45   | -      | 110     | 195     |            |          | 2,066  | 1 | STK  |
| KLLSB110.300.45   | -      | 110     | 295     |            |          | 2,217  | 1 | STK  |
| KLLSB110.400.45   | -      | 110     | 395     |            |          | 2,369  | 1 | STK  |
| KLLSB110.450.45   | -      | 110     | 445     |            |          | 2,444  | 1 | STK  |
| KLLSB110.500.45   | -      | 110     | 495     |            |          | 2,520  | 1 | STK  |
| KLLSB110.600.45   | -      | 110     | 595     |            |          | 2,671  | 1 | STK  |
| KLLSB110.750.45   | SZ     | 110     | 750     | 1,25       |          | 2,839  | 1 | STK  |
| KLLSB110.800.45   | SZ     | 110     | 800     | 1,25       |          | 2,926  | 1 | STK  |
| ZMKLLSB60.150.45  | DF     | 60      | 150     | 1,25       |          | 1,101  | 1 | STK  |
| KLLSB110.900.45   | SZ     | 110     | 900     | 1,25       |          | 3,100  | 1 | STK  |
| ZMKLLSB60.200.45  | DF     | 60      | 200     | 1,25       |          | 1,189  | 1 | STK  |
| ZMKLLSB60.300.45  | DF     | 60      | 300     | 1,25       |          | 1,363  | 1 | STK  |
| ZMKLLSB60.400.45  | DF     | 60      | 400     | 1,25       |          | 1,537  | 1 | STK  |
| ZMKLLSB60.450.45  | DF     | 60      | 450     | 1,25       |          | 1,624  | 1 | STK  |
| ZMKLLSB60.500.45  | DF     | 60      | 500     | 1,25       |          | 1,711  | 1 | STK  |
| ZMKLLSB60.600.45  | DF     | 60      | 600     | 1,25       |          | 1,886  | 1 | STK  |
| ZMKLLSB60.750.45  | DF     | 60      | 750     | 1,25       |          | 2,147  | 1 | STK  |
| ZMKLLSB60.800.45  | DF     | 60      | 800     | 1,25       |          | 2,234  | 1 | STK  |
| ZMKLLSB60.900.45  | DF     | 60      | 900     | 1,25       |          | 2,409  | 1 | STK  |
| ZMKLLSB110.150.45 | DF     | 110     | 150     | 1,25       |          | 1,793  | 1 | STK  |
| ZMKLLSB110.200.45 | DF     | 110     | 200     | 1,25       |          | 1,880  | 1 | STK  |
| ZMKLLSB110.300.45 | DF     | 110     | 300     | 1,25       |          | 2,055  | 1 | STK  |
| ZMKLLSB110.400.45 | DF     | 110     | 400     | 1,25       |          | 2,229  | 1 | STK  |
| ZMKLLSB110.450.45 | DF     | 110     | 450     | 1,25       |          | 2,316  | 1 | STK  |
| ZMKLLSB110.500.45 | DF     | 110     | 500     | 1,25       |          | 2,403  | 1 | STK  |
| ZMKLLSB110.600.45 | DF     | 110     | 600     | 1,25       |          | 2,577  | 1 | STK  |
| ZMKLLSB110.750.45 | DF     | 110     | 750     | 1,25       |          | 2,839  | 1 | STK  |
| ZMKLLSB110.800.45 | DF     | 110     | 800     | 1,25       |          | 2,926  | 1 | STK  |
| ZMKLLSB110.900.45 | DF     | 110     | 900     | 1,25       |          | 3,100  | 1 | STK  |

Minimum number bolts and nuts VM6.10: 8 pieces.

#### Legend finish

- SZ = Sendzimir
- DF = Defender