

KLLX

Cross-over for KLL



Radius: 300 mm

	150	200	300	400	500	600
A	1021	1071	1171	1271	1371	1471

Fix with:



Toothed round head bolt / flange nut
VM

Reference	Finish	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Unit
KLLX60.150	-	60	141			3,131	1	STK
KLLX60.200	-	60	191			3,232	1	STK
KLLX60.300	-	60	291			4,421	1	STK
KLLX60.400	-	60	391			4,875	1	STK
KLLX60.450	-	60	443			5,102	1	STK
KLLX60.500	-	60	491			5,329	1	STK
KLLX60.600	-	60	591			5,782	1	STK
KLLX60.750	SZ	60	750	1,25		8,530	1	STK
KLLX60.800	SZ	60	800	1,25		8,890	1	STK
KLLX60.900	SZ	60	900	1,25		9,611	1	STK
KLLX110.150	-	110	145			4,537	1	STK
KLLX110.200	-	110	195			4,796	1	STK
KLLX110.300	-	110	295			5,985	1	STK
KLLX110.400	-	110	395			6,439	1	STK
KLLX110.450	-	110	445			6,666	1	STK
KLLX110.500	-	110	495			6,893	1	STK
KLLX110.600	-	110	595			7,346	1	STK
KLLX110.750	-	110	750			8,446	1	STK
KLLX110.800	SZ	110	800	1,25		10,408	1	STK
KLLX110.900	-	110	900			9,546	1	STK
ZMKLLX60.150	DF	60	150	1,25		3,985	1	STK
ZMKLLX60.200	DF	60	200	1,25		4,258	1	STK
ZMKLLX60.300	DF	60	300	1,25		4,965	1	STK
ZMKLLX60.400	DF	60	400	1,25		5,570	1	STK
ZMKLLX60.450	DF	60	450	1,25		5,872	1	STK
ZMKLLX60.500	DF	60	500	1,25		6,451	1	STK
ZMKLLX60.600	DF	60	600	1,25		7,113	1	STK
ZMKLLX60.750	DF	60	750	1,25		8,530	1	STK
ZMKLLX60.800	DF	60	800	1,25		8,890	1	STK
ZMKLLX60.900	DF	60	900	1,25		9,611	1	STK
ZMKLLX110.150	DF	110	150	1,25		5,502	1	STK
ZMKLLX110.200	DF	110	200	1,25		5,775	1	STK
ZMKLLX110.300	DF	110	300	1,25		6,483	1	STK
ZMKLLX110.400	DF	110	400	1,25		7,087	1	STK
ZMKLLX110.450	DF	110	450	1,25		7,390	1	STK
ZMKLLX110.500	DF	110	500	1,25		7,969	1	STK
ZMKLLX110.600	DF	110	600	1,25		8,631	1	STK
ZMKLLX110.750	DF	110	750	1,25		10,047	1	STK
ZMKLLX110.800	DF	110	800	1,25		10,408	1	STK
ZMKLLX110.900	DF	110	900	1,25		11,129	1	STK

Minimum number bolts and nuts VM6.10: 16 pieces.

Legend finish
- SZ = Sendzimir
- DF = Defender