


KLM125SB45

Internal riser for KLM125



Radius: 600 mm

Reference	Finish	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	Unit	Unit
KLM125SB45.150	SZ	125	158			3,284	1	STK
KLM125SB45.200	SZ	125	208			3,400	1	STK
KLM125SB45.300	SZ	125	308			3,630	1	STK
KLM125SB45.400	SZ	125	408			3,860	1	STK
KLM125SB45.450	SZ	125	458			3,976	1	STK
KLM125SB45.500	SZ	125	508			4,091	1	STK
KLM125SB45.600	SZ	125	608			4,321	1	STK
KLM125SB45.750	SZ	125	758			4,667	1	STK
KLM125SB45.800	SZ	125	808			4,782	1	STK
KLM125SB45.900	SZ	125	908			5,012	1	STK
KLM125SB45.1000	SZ	125	1008			5,243	1	STK
ZMKLM125SB45.150	DF	125	158			3,284	1	STK
ZMKLM125SB45.200	DF	125	208			3,400	1	STK
ZMKLM125SB45.300	DF	125	308			3,630	1	STK
ZMKLM125SB45.400	DF	125	408			3,860	1	STK
ZMKLM125SB45.450	DF	125	458			3,976	1	STK
ZMKLM125SB45.500	DF	125	508			4,091	1	STK
ZMKLM125SB45.600	DF	125	608			4,321	1	STK
ZMKLM125SB45.750	DF	125	758			4,667	1	STK
ZMKLM125SB45.800	DF	125	808			4,782	1	STK
ZMKLM125SB45.900	DF	125	908			5,012	1	STK
ZMKLM125SB45.1000	DF	125	1008			5,243	1	STK

Fix with:



Round head square neck bolt (DIN 603) RBK

Flange nut (DIN 6923) RM

Minimum number bolts and nuts: 8 pieces.

Legend finish
- SZ = Sendzimir
- DF = Defender