


# SLOS

## Partition



| Reference          | Finish | ↑<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/m  | 📦   | Unit |
|--------------------|--------|---------|---------|------------|---------|-------|-----|------|
| <b>SLOS35</b>      | SZ     | 28      |         |            | 3000    | 0,330 | 150 | M    |
| <b>SLOS60</b>      | SZ     | 53      |         |            | 3000    | 0,511 | 120 | M    |
| <b>SLOS60.2000</b> | -      | 53      |         |            | 1900    | 0,793 | 520 | M    |
| <b>SLOS85</b>      | SZ     | 78      |         |            | 3000    | 0,680 | 60  | M    |
| <b>SLOS110</b>     | SZ     | 103     |         |            | 3000    | 0,820 | 30  | M    |
| <b>ZMSLOS35</b>    | DF     | 28      |         |            | 3000    | 0,257 | 150 | M    |
| <b>ZMSLOS60</b>    | DF     | 60      |         |            | 3000    | 0,397 | 120 | M    |
| <b>ZMSLOS85</b>    | DF     | 78      |         |            | 3000    | 0,529 | 60  | M    |
| <b>ZMSLOS110</b>   | DF     | 103     |         |            | 3000    | 0,638 | 30  | M    |

### Fix with:



Toothed round  
head bolt  
RB

Sliding nut for  
supporting profile  
PNP06-  
PNP12A

Fixing set: 1 per meter.

**Legend finish**  
- SZ = Sendzimir  
- DF = Defender