

# KDVKK3

## Hinged cover square, universal



Build-in frame + hinged cover + cable outlet unit

Color: Grey RAL 7011/ Black RAL 9011

Max. load: 1500 N (small surface area)

Max. load: 2000 N (large surface area)

Active condition: IP 20

Non-active condition: IP 30

Depth of floor covering: Min. 5 mm - Max. 12 mm

Thickness steel plate : 3 mm

| Reference            | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Unit |
|----------------------|---------|---------|------------|---------|--------|---|------|
| <b>KDVKK3.5-7011</b> |         | 267     |            | 267     | 2,200  | 6 | STK  |
| <b>KDVKK3.5-9011</b> |         | 267     |            | 267     | 2,200  | 6 | STK  |



Tested to EN 50085-2-2.

Hinged cover for 3 compartments.

Standard depth of floor covering is 5 mm and can be reduced by fitting packers OHEV3.2 and/or OHEV3.5.

Replace the clamps of the hinged cover by the enclosed clamps of the DOVG.

Hinged cover is provided with 2 cable outlets with integrated push lever and cable organiser.

Hinged cover must not be earthed.

For use in dry floors only.

