

# BTFCL

## Horizontal bend 90°

Non-perforated base  
Return flanges


Radius: 250 mm



### Fix with:



Joining plate  
V85.200



Joining plate  
V60.200



Joining plate  
V35.200

| Reference           | ↑<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Unit |
|---------------------|---------|---------|------------|---------|--------|---|------|
| <b>BTFCL60.100</b>  | 60      | 100     | 2          |         | 3,000  | 1 | STK  |
| <b>BTFCL60.150</b>  | 60      | 150     | 2          |         | 3,830  | 1 | STK  |
| <b>BTFCL60.200</b>  | 60      | 200     | 2          |         | 4,730  | 1 | STK  |
| <b>BTFCL60.250</b>  | 60      | 250     | 2          |         | 5,710  | 1 | STK  |
| <b>BTFCL60.300</b>  | 60      | 300     | 2          |         | 6,740  | 1 | STK  |
| <b>BTFCL85.100</b>  | 85      | 100     | 2          |         | 3,630  | 1 | STK  |
| <b>BTFCL85.150</b>  | 85      | 150     | 2          |         | 4,500  | 1 | STK  |
| <b>BTFCL85.200</b>  | 85      | 200     | 2          |         | 5,430  | 1 | STK  |
| <b>BTFCL85.250</b>  | 85      | 250     | 2          |         | 6,430  | 1 | STK  |
| <b>BTFCL85.300</b>  | 85      | 300     | 2          |         | 7,490  | 1 | STK  |
| <b>BTFCL110.150</b> | 110     | 150     | 2          |         | 5,150  | 1 | STK  |
| <b>BTFCL110.200</b> | 110     | 200     | 2          |         | 6,120  | 1 | STK  |
| <b>BTFCL110.250</b> | 110     | 250     | 2          |         | 7,150  | 1 | STK  |
| <b>BTFCL110.300</b> | 110     | 300     | 2          |         | 8,240  | 1 | STK  |