


COMEGACLU290

Open suspension bracket universal



Useful for direct mounting to the ceiling or with threaded rod TIM8 or TIM10.

Standard finish	Pre-galvanised
Optional finish	Hot-dip galvanised
Optional finish	Coating

	Max. load (in daN)	A
COMEGACLU290.100	70	145
COMEGACLU290.150	60	145
COMEGACLU290.200	60	145
COMEGACLU290.250	50	195
COMEGACLU290.300	50	195
COMEGACLU290.400	40	245

HD	Reference	↑ mm	↔ mm	≡ mm	↔ mm	kg /stk	📦	Stock	Unit
HD	COMEGACLU290.100	290	169			0,520	12	v	STK
HD	COMEGACLU290.150	290	194			0,560	12	v	STK
HD	COMEGACLU290.200	290	244			0,620	12	v	STK
HD	COMEGACLU290.250	290	294			0,760	6	v	STK
HD	COMEGACLU290.300	290	344			0,820	6	v	STK
HD	COMEGACLU290.400	290	444			0,930	6	v	STK

To order per full packaging.

Fixing of the cable tray by VM6.20.

Use the VOMEGA to avoid compression of the profile.

Max. load (in daN): uniformly distributed over complete width of cantilever brackets.

Do not use with: VFUL30.065, VFUL35.150, VFU35.150, VFUL 60.050.