


OBZ130

Open suspension bracket



Useful for direct mounting to the ceiling or with threaded rod TIM8 or TIM10.

Standard finish	Electro zinc-plated
Optional finish	Hot-dip galvanised
Optional finish	Coating

	Max. load (in daN)	A	B
OBZ130.075	80	64	42,5
OBZ130.100	40	80	59,5
OBZ130.150	50	105	84,5
OBZ130.200	30	130	109,5
OBZ130.250	50	155	134,5
OBZ130.300	40	180	159,5
OBZ130.400	30	230	209,5

HD	Reference	↑ mm	↔ mm	≡ mm	↔ mm	kg /stk	📦	Stock	Unit
HD	OBZ130.075	132	102			0,39	12	v	STK
HD	OBZ130.100	132	125			0,45	12	v	STK
HD	OBZ130.150	132	177			0,57	12	v	STK
HD	OBZ130.200	132	227			0,67	12	v	STK
HD	OBZ130.250	132	281			1,02	6	v	STK
HD	OBZ130.300	132	331			1,18	6	v	STK
HD	OBZ130.400	132	431			1,461	6	v	STK

To order per full packaging.

Fixing of the cable tray by VM6.20.

Max. load (in daN): uniformly distributed over complete width of cantilever brackets.