


HDHSLECL

Single ceiling profile clippable



Ceiling profile 41.21
Welded headplate: 135x135 mm

Max. load: 1000 daN
Thickness head plate: 4 mm

| Reference | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|---------------------|---------|---------|------------|---------|--------|----|------|
| HDHSLECL200 | 210 | 21 | | | 0,740 | 25 | STK |
| HDHSLECL300 | 300 | 21 | | | 0,850 | 1 | STK |
| HDHSLECL400 | 420 | 21 | | | 1,010 | 1 | STK |
| HDHSLECL500 | 510 | 21 | | | 1,130 | 1 | STK |
| HDHSLECL600 | 600 | 21 | | | 1,230 | 1 | STK |
| HDHSLECL800 | 810 | 21 | | | 1,450 | 1 | STK |
| HDHSLECL1000 | 1020 | 21 | | | 1,750 | 1 | STK |
| HDHSLECL1200 | 1200 | 21 | | | 1,950 | 1 | STK |

For single and double sided fixing of the bracket KCL and for single sided fixing of the other brackets WKST, WKML and HDWK using sliding nut PNP10 and hexagonal bolt B10.20.
Protection cap in yellow PVC: DOP41.21.