

# LOMEGACLU150

## Wall bracket universal



|                  | Max. load (in daN) |
|------------------|--------------------|
| LOMEGACLU150.100 | 110                |
| LOMEGACLU150.150 | 100                |
| LOMEGACLU150.200 | 90                 |
| LOMEGACLU150.250 | 80                 |
| LOMEGACLU150.300 | 70                 |
| LOMEGACLU150.400 | 50                 |
| LOMEGACLU150.500 | 40                 |
| LOMEGACLU150.600 | 30                 |

| Reference                 | Finish | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦  | Unit |
|---------------------------|--------|---------|---------|------------|---------|--------|----|------|
| <b>ZMLOMEGACLU150.100</b> | DF     | 145     | 155     | 1,5        |         | 0,300  | 12 | STK  |
| <b>ZMLOMEGACLU150.150</b> | DF     | 145     | 195     | 1,5        |         | 0,320  | 12 | STK  |
| <b>ZMLOMEGACLU150.200</b> | DF     | 145     | 245     | 1,5        |         | 0,340  | 12 | STK  |
| <b>ZMLOMEGACLU150.250</b> | DF     | 145     | 295     | 1,5        |         | 0,450  | 12 | STK  |
| <b>ZMLOMEGACLU150.300</b> | DF     | 145     | 345     | 1,5        |         | 0,490  | 12 | STK  |
| <b>ZMLOMEGACLU150.400</b> | DF     | 145     | 445     | 1,5        |         | 0,540  | 6  | STK  |
| <b>ZMLOMEGACLU150.500</b> | DF     | 145     | 545     | 1,5        |         | 0,710  | 6  | STK  |
| <b>ZMLOMEGACLU150.600</b> | DF     | 145     | 645     | 1,5        |         | 0,770  | 6  | STK  |

Fixing of the cable tray by VM6.20.

Use the VOMEGA to avoid compression of the profile.

Max. load (in daN): uniformly distributed over complete width of cantilever brackets.

Do not use with: VFUL30.065, VFUL35.150, VFU35.150, VFUL 60.050.

### Legend finish

- DF = Defender