

# HDHSMU50

## Ceiling profile medium heavy



Suspension support with U-profile 50 x 50 mm  
Welded head plate 135 x 135 mm  
Thickness of head plate: 5 mm  
Max. load: 2100daN

Max. load: 2100 daN

| Reference            | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦  | Unit |
|----------------------|---------|---------|------------|---------|--------|----|------|
| <b>HDHSMU50.200</b>  | 200     | 50      |            |         | 0,940  | 20 | STK  |
| <b>HDHSMU50.300</b>  | 300     | 50      |            |         | 1,160  | 1  | STK  |
| <b>HDHSMU50.400</b>  | 400     | 50      |            |         | 1,380  | 1  | STK  |
| <b>HDHSMU50.500</b>  | 500     | 50      |            |         | 1,610  | 1  | STK  |
| <b>HDHSMU50.600</b>  | 600     | 50      |            |         | 1,830  | 1  | STK  |
| <b>HDHSMU50.800</b>  | 800     | 50      |            |         | 2,270  | 1  | STK  |
| <b>HDHSMU50.1000</b> | 1000    | 50      |            |         | 2,710  | 1  | STK  |
| <b>HDHSMU50.1200</b> | 1200    | 50      |            |         | 3,150  | 1  | STK  |
| <b>HDHSMU50.1500</b> | 1500    | 50      |            |         | 3,820  | 1  | STK  |

Protective cap in yellow PVC: DOPHSMU