

CS45SHY

Wire suspension Y-split with hooks



Max. load: 45 daN

| Reference | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|--------------------|---------|---------|------------|---------|--------|----|------|
| CS45SH150Y1 | | 150 | | 1000 | 0,100 | 10 | STK |
| CS45SH150Y2 | | 150 | | 2000 | 0,100 | 10 | STK |
| CS45SH150Y3 | | 150 | | 3000 | 0,100 | 10 | STK |
| CS45SH300Y1 | | 300 | | 1000 | 0,150 | 10 | STK |
| CS45SH300Y2 | | 300 | | 2000 | 0,150 | 10 | STK |
| CS45SH300Y3 | | 300 | | 3000 | 0,150 | 10 | STK |
| CS45SH500Y1 | | 500 | | 1000 | 0,250 | 10 | STK |
| CS45SH500Y2 | | 500 | | 2000 | 0,250 | 10 | STK |
| CS45SH500Y3 | | 500 | | 3000 | 0,250 | 10 | STK |
| CS45SH800Y1 | | 800 | | 1000 | 0,400 | 10 | STK |
| CS45SH800Y2 | | 800 | | 2000 | 0,400 | 10 | STK |
| CS45SH800Y3 | | 800 | | 3000 | 0,400 | 10 | STK |