

I6KLM100

Cable ladder height 100



Cable ladder for large support distances up to 8 metres
Perforated C rungs 41 x 21

Usable inner height: 102 mm

Rung distance: 250 mm

To order: Length 6000 mm

Reference	Finish	↑ mm	↔ mm	→ ← mm	↔ mm	kg/m	Unit
I6KLM100.150	SS	100	168	1,5 MM	6000	5,135	60 M
I6KLM100.200	SS	100	218	1,5 MM	6000	5,263	60 M
I6KLM100.300	SS	100	318	1,5 MM	6000	5,519	60 M
I6KLM100.400	SS	100	418	1,5 MM	6000	5,775	60 M
I6KLM100.450	SS	100	468	1,5 MM	6000	5,903	60 M
I6KLM100.500	SS	100	518	1,5 MM	6000	6,031	60 M
I6KLM100.600	SS	100	618	1,5 MM	6000	6,287	60 M
I6KLM100.750	SS	100	768	1,5 MM	6000	6,671	60 M
I6KLM100.800	SS	100	818	1,5 MM	6000	6,799	60 M
I6KLM100.900	SS	100	918	1,5 MM	6000	7,055	60 M
I6KLM100.1000	SS	100	1018	1,5 MM	6000	7,311	60 M

CHARACTERISTICS

- strong
- usable inner height 102 mm, ideal for large diameter cables
- no further coupling holes are required if the cable ladder is cut
- no joiners are required to attach accessories such as bends, tees etc.
- rungs are perforated to enable efficient attachment of cables
- partition (I6SLOS60) can be fixed to the cable ladder with a sliding nut (I6PNP06) and pan head bolt (I6RB6.20).

TECHNICAL INFORMATION

Side walls are constructed from S profile with a return flange and are continuously perforated

- C-profile rungs are fixed at 250 mm intervals.
- rungs are mechanically attached to the side wall of the cable ladder.
- rungs are alternately placed with openings upwards and downwards.

Pickled and passivated.

Legend finish

- SS = Stainless steel