


I6KLM125X

Cross-over for I6KLM125



Fix with:



Round head
square neck bolt
(DIN 603)
I6RBK

Nut (DIN 934)
I6M



Giant washer
(DIN 125-1 A)
I6RO

Radius: 600 mm

| Reference | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|----------------------|---------|---------|------------|---------|--------|---|------|
| I6KLM125X150 | 125 | 150 | | | 14,205 | 1 | STK |
| I6KLM125X200 | 125 | 208 | | | 14,749 | 1 | STK |
| I6KLM125X300 | 125 | 308 | | | 15,838 | 1 | STK |
| I6KLM125X400 | 125 | 408 | | | 16,927 | 1 | STK |
| I6KLM125X450 | 125 | 450 | | | 17,793 | 1 | STK |
| I6KLM125X500 | 125 | 508 | | | 18,377 | 1 | STK |
| I6KLM125X600 | 125 | 608 | | | 22,957 | 1 | STK |
| I6KLM125X750 | 125 | 750 | | | 24,858 | 1 | STK |
| I6KLM125X800 | 125 | 800 | | | 25,492 | 1 | STK |
| I6KLM125X900 | 125 | 900 | | | 27,420 | 1 | STK |
| I6KLM125X1000 | 125 | 1000 | | | 28,764 | 1 | STK |

Minimum number bolts and nuts: 16 pieces.

Pickled and passivated.