

COMEGACLU170

Open suspension bracket universal



Useful for direct mounting to the ceiling or with threaded rod TIM8 or TIM10.

| | Max. load (in daN) | A |
|------------------|--------------------|-----|
| COMEGACLU170.150 | 60 | 145 |
| COMEGACLU170.200 | 60 | 145 |
| COMEGACLU170.300 | 50 | 195 |
| COMEGACLU170.400 | 40 | 245 |

| Reference | Finish | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unit |
|---------------------------|--------|---------|---------|------------|---------|--------|----|------|
| ZMCOMEGACLU170.150 | DF | 170 | 182 | 1,5 | | 0,460 | 12 | STK |
| ZMCOMEGACLU170.200 | DF | 170 | 232 | 1,5 | | 0,540 | 12 | STK |
| ZMCOMEGACLU170.300 | DF | 170 | 332 | 1,5 | | 0,700 | 6 | STK |
| ZMCOMEGACLU170.400 | DF | 170 | 432 | 1,5 | | 0,860 | 6 | STK |

Fixing of the cable tray by VM6.20.

Use the VOMEGA to avoid compression of the profile.

Max. load (in daN): uniformly distributed over complete width of cantilever brackets.

Do not use with: VFUL30.065, VFUL35.150, VFU35.150, VFUL 60.050

Legend finish

- DF = Defender