


# VB90

## Low elbow 90°



Slides over the cable trays

Radius: 100 mm

To order: Height 35 mm - 85 mm - 110 mm (only in SZ et HD)

### Fix with:



Toothed round head bolt / flange nut  
VM



Round head square neck bolt / flange nut  
VMK

Reference	Finish	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unit
<b>ZMVB90.110.100</b>	DF	110	100	0,75		0,813	1	STK
<b>ZMVB90.110.150</b>	DF	110	150	0,75		0,912	1	STK
<b>ZMVB90.110.200</b>	DF	110	200	0,75		1,010	1	STK
<b>ZMVB90.110.300</b>	DF	110	300	0,75		1,208	1	STK
<b>ZMVB90.110.400</b>	DF	110	400	0,75		1,405	1	STK
<b>ZMVB90.110.500</b>	DF	110	500	0,75/0,9		1,885	1	STK
<b>ZMVB90.110.600</b>	DF	110	600	0,75/0,9		2,139	1	STK
<b>ZMVB90.85.100</b>	DF	85	100	0,75		0,675	1	STK
<b>ZMVB90.85.150</b>	DF	85	150	0,75		0,774	1	STK
<b>ZMVB90.85.200</b>	DF	85	200	0,75		0,872	1	STK
<b>ZMVB90.85.300</b>	DF	85	300	0,75		1,070	1	STK
<b>ZMVB90.85.400</b>	DF	85	400	0,75		1,267	1	STK
<b>ZMVB90.85.500</b>	DF	85	500	0,75/0,9		1,747	1	STK
<b>ZMVB90.85.600</b>	DF	85	600	0,75/0,9		2,001	1	STK
<b>ZMVB90.60.050</b>	DF	60	50			0,449	1	STK
<b>ZMVB90.60.075</b>	DF	60	75			0,498	1	STK
<b>ZMVB90.60.100</b>	DF	60	100			0,548	1	STK
<b>ZMVB90.60.150</b>	DF	60	150			0,646	1	STK
<b>ZMVB90.60.200</b>	DF	60	200			0,745	1	STK
<b>ZMVB90.60.300</b>	DF	60	300			0,942	1	STK
<b>ZMVB90.60.400</b>	DF	60	400			1,140	1	STK
<b>ZMVB90.60.500</b>	DF	60	501,4	0,9		1,430	1	STK
<b>ZMVB90.60.600</b>	DF	60	601,4	0,9		1,600	1	STK

Minimum number bolts and nuts: 8 pieces.

### Legend finish

- DF = Defender