

I6KLM100B

Courbe horizontale à 90° pour I6KLM100



A fixer avec:



Rondelle (DIN
125-1 A)
I6RO



Erou (DIN 934)
I6M



Boulon à collet
I6RBK

Rayon: 600 mm

| Référence | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|----------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM100B150 | 100 | B150 | | | 5,456 | 1 | STK |
| I6KLM100B200 | 100 | 208 | | | 5,860 | 1 | STK |
| I6KLM100B300 | 100 | 308 | | | 6,669 | 1 | STK |
| I6KLM100B400 | 100 | 408 | | | 7,477 | 1 | STK |
| I6KLM100B450 | 100 | 450 | | | 7,881 | 1 | STK |
| I6KLM100B500 | 100 | 508 | | | 9,031 | 1 | STK |
| I6KLM100B600 | 100 | 608 | | | 9,093 | 1 | STK |
| I6KLM100B750 | 100 | 750 | | | 11,432 | 1 | STK |
| I6KLM100B800 | 100 | 800 | | | 11,915 | 1 | STK |
| I6KLM100B900 | 100 | 900 | | | 12,881 | 1 | STK |
| I6KLM100B1000 | 100 | 1000 | | | 13,847 | 1 | STK |

Nombre minimal des boulons et des écrous: 8 pièces.

Décapé et passivé.