

I6KLM100B45

Courbe horizontale à 45° pour I6KLM100



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecoux elargi (DIN
6923)
RM

Rayon: 600 mm

| Référence | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|-------------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM100B45.150 | 100 | 150 | | | 3,498 | 1 | STK |
| I6KLM100B45.200 | 100 | 200 | | | 3,720 | 1 | STK |
| I6KLM100B45.300 | 100 | 300 | | | 4,163 | 1 | STK |
| I6KLM100B45.400 | 100 | 400 | | | 4,607 | 1 | STK |
| I6KLM100B45.450 | 100 | 450 | | | 4,828 | 1 | STK |
| I6KLM100B45.500 | 100 | 500 | | | 5,417 | 1 | STK |
| I6KLM100B45.600 | 100 | 600 | | | 5,939 | 1 | STK |
| I6KLM100B45.750 | 100 | 750 | | | 6,722 | 1 | STK |
| I6KLM100B45.800 | 100 | 800 | | | 6,983 | 1 | STK |
| I6KLM100B45.900 | 100 | 900 | | | 7,505 | 1 | STK |
| I6KLM100B45.1000 | 100 | 1000 | | | 8,788 | 1 | STK |

Nombre minimal des boulons et des écrous: 8 pièces.