

I6KLM125B

Courbe horizontale à 90° pour I6KLM125



A fixer avec:



Boulon à collet
I6RBK

Erou (DIN 934)
I6M



Rondelle (DIN
125-1 A)
I6RO

Rayon: 600 mm

| Référence | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Unité |
|----------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM125B150 | 125 | 150 | | | 6,456 | 1 | STK |
| I6KLM125B200 | 125 | 208 | | | 6,884 | 1 | STK |
| I6KLM125B300 | 125 | 308 | | | 7,739 | 1 | STK |
| I6KLM125B400 | 125 | 408 | | | 8,595 | 1 | STK |
| I6KLM125B450 | 125 | 450 | | | 9,023 | 1 | STK |
| I6KLM125B500 | 125 | 508 | | | 9,450 | 1 | STK |
| I6KLM125B600 | 125 | 608 | | | 10,306 | 1 | STK |
| I6KLM125B750 | 125 | 750 | | | 12,714 | 1 | STK |
| I6KLM125B800 | 125 | 800 | | | 13,220 | 1 | STK |
| I6KLM125B900 | 125 | 900 | | | 14,234 | 1 | STK |
| I6KLM125B1000 | 125 | 1000 | | | 18,323 | 1 | STK |

Nombre minimal des boulons et des écrous: 8 pièces.

Décapé et passivé.