


# I6KLM125SB45

## Courbe intérieure pour I6KLM125



Rayon: 600 mm

Référence	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unité
<b>I6KLM125SB45.150</b>	125	150			3,367	1	STK
<b>I6KLM125SB45.200</b>	125	200			3,486	1	STK
<b>I6KLM125SB45.300</b>	125	300			3,722	1	STK
<b>I6KLM125SB45.400</b>	125	400			3,958	1	STK
<b>I6KLM125SB45.450</b>	125	450			4,077	1	STK
<b>I6KLM125SB45.500</b>	125	500			4,195	1	STK
<b>I6KLM125SB45.600</b>	125	600			4,430	1	STK
<b>I6KLM125SB45.750</b>	125	750			4,785	1	STK
<b>I6KLM125SB45.800</b>	125	800			4,903	1	STK
<b>I6KLM125SB45.900</b>	125	900			5,139	1	STK
<b>I6KLM125SB45.1000</b>	125	1000			5,376	1	STK

### A fixer avec:



Boulon à collet  
(DIN 603)  
RBK

Ecoux elargi (DIN  
6923)  
RM

Nombre minimal des boulons et des écrous: 8 pièces.