


# I6KLM125VB45

## Courbe extérieure pour I6KLM125

Rayon: 600 mm



**A fixer avec:**



Eroux elargi (DIN 6923)  
RM

Boulon à collet (DIN 603)  
RBK

| Référence                | ↑<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Unité |
|--------------------------|---------|---------|------------|---------|--------|---|-------|
| <b>I6KLM125VB45.150</b>  | 125     | 150     |            |         | 3,281  | 1 | STK   |
| <b>I6KLM125VB45.200</b>  | 125     | 200     |            |         | 3,359  | 1 | STK   |
| <b>I6KLM125VB45.300</b>  | 125     | 300     |            |         | 3,517  | 1 | STK   |
| <b>I6KLM125VB45.400</b>  | 125     | 400     |            |         | 3,675  | 1 | STK   |
| <b>I6KLM125VB45.450</b>  | 125     | 450     |            |         | 3,753  | 1 | STK   |
| <b>I6KLM125VB45.500</b>  | 125     | 500     |            |         | 3,832  | 1 | STK   |
| <b>I6KLM125VB45.600</b>  | 125     | 600     |            |         | 3,990  | 1 | STK   |
| <b>I6KLM125VB45.750</b>  | 125     | 750     |            |         | 4,225  | 1 | STK   |
| <b>I6KLM125VB45.800</b>  | 125     | 800     |            |         | 4,304  | 1 | STK   |
| <b>I6KLM125VB45.900</b>  | 125     | 900     |            |         | 4,462  | 1 | STK   |
| <b>I6KLM125VB45.1000</b> | 125     | 1000    |            |         | 4,619  | 1 | STK   |

Nombre minimal des boulons et des écrous: 8 pièces.