

D Couvercle universel



Pour cheminements horizontaux et verticaux

| Référence | Finition | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/m | | Unité |
|---------------|----------|---------|---------|------------|---------|-------|-----|-------|
| D050 | SZ | 10 | 50 | | 3000 | 0,328 | 30 | M |
| D075 | SZ | 10 | 75 | | 2000 | 0,446 | 20 | M |
| D100 | SZ | 10 | 100 | | 2000 | 0,564 | 20 | M |
| D100.3 | SZ | 10 | 100 | | 3000 | 0,563 | 300 | M |
| D150 | SZ | 10 | 150 | | 2000 | 0,799 | 20 | M |
| D200 | DF | 10 | 200 | | 2000 | 1,035 | 20 | M |
| D200.3 | SZ | 10 | 200 | | 3000 | 1,035 | 300 | M |
| D250 | SZ | 10 | 250 | | 2000 | 1,481 | 20 | M |
| D300 | SZ | 10 | 300 | | 2000 | 1,756 | 20 | M |
| D400 | SZ | 10 | 400 | | 2000 | 2,960 | 20 | M |
| D500 | SZ | 10 | 500 | | 2000 | 3,667 | 2 | M |
| D600 | SZ | 10 | 600 | | 2000 | 4,373 | 2 | M |
| ZMD050 | DF | 10 | 50 | | 3000 | 0,328 | 30 | M |
| ZMD075 | DF | 10 | 75 | | 2000 | 0,446 | 20 | M |
| ZMD100 | DF | 10 | 100 | | 2000 | 0,564 | 20 | M |
| ZMD150 | DF | 10 | 150 | | 2000 | 0,799 | 20 | M |
| ZMD200 | DF | 10 | 200 | | 2000 | 1,035 | 20 | M |
| ZMD250 | DF | 10 | 250 | | 2000 | 1,481 | 20 | M |
| ZMD300 | DF | 10 | 300 | | 2000 | 1,756 | 20 | M |
| ZMD400 | DF | 10 | 400 | | 2000 | 2,960 | 20 | M |
| ZMD500 | DF | 10 | 500 | | 2000 | 3,667 | 2 | M |
| ZMD600 | DF | 10 | 600 | | 2000 | 4,373 | 2 | M |

A fixer avec:



Attache couvercle
DCL

Attache couvercle
imperdable
DCO

Pour des largeurs > 400 mm: le couvercle est pourvu de nervures de renfort.

Légende de la finition

- SZ = Sendzimir
- DF = Defender