

# BTFCL

## Courbe horizontale à 90°


Fond lisse  
Bords rabattus

Rayon: 250 mm




Référence	↑ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Unité
<b>BTFCL60.100</b>	60	100	2		3,000	1	STK
<b>BTFCL60.150</b>	60	150	2		3,830	1	STK
<b>BTFCL60.200</b>	60	200	2		4,730	1	STK
<b>BTFCL60.250</b>	60	250	2		5,710	1	STK
<b>BTFCL60.300</b>	60	300	2		6,740	1	STK
<b>BTFCL85.100</b>	85	100	2		3,630	1	STK
<b>BTFCL85.150</b>	85	150	2		4,500	1	STK
<b>BTFCL85.200</b>	85	200	2		5,430	1	STK
<b>BTFCL85.250</b>	85	250	2		6,430	1	STK
<b>BTFCL85.300</b>	85	300	2		7,490	1	STK
<b>BTFCL110.150</b>	110	150	2		5,150	1	STK
<b>BTFCL110.200</b>	110	200	2		6,120	1	STK
<b>BTFCL110.250</b>	110	250	2		7,150	1	STK
<b>BTFCL110.300</b>	110	300	2		8,240	1	STK

### A fixer avec:



Eclisse à  
boulonner  
V85.200



Eclisse à  
boulonner  
V60.200



Eclisse à  
boulonner  
V35.200