

BTFCCL

Courbe horizontale à 90°

Fond lisse
Bords rabattus

Rayon: 250 mm

Exec. Std.

Sendzimir


Mat. Opt.

Galvanisé à chaud




HD	Référence	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
HD	BTFCCL60.100	60	100	2		3,000	1		STK
HD	BTFCCL60.150	60	150	2		3,830	1		STK
HD	BTFCCL60.200	60	200	2		4,730	1		STK
HD	BTFCCL60.250	60	250	2		5,710	1		STK
HD	BTFCCL60.300	60	300	2		6,740	1		STK
HD	BTFCCL85.100	85	100	2		3,630	1		STK
HD	BTFCCL85.150	85	150	2		4,500	1		STK
HD	BTFCCL85.200	85	200	2		5,430	1		STK
HD	BTFCCL85.250	85	250	2		6,430	1		STK
HD	BTFCCL85.300	85	300	2		7,490	1		STK
HD	BTFCCL110.150	110	150	2		5,150	1		STK
HD	BTFCCL110.200	110	200	2		6,120	1		STK
HD	BTFCCL110.250	110	250	2		7,150	1		STK
HD	BTFCCL110.300	110	300	2		8,240	1		STK

A fixer avec:



Eclisse à
boulonner
V85.200



Eclisse à
boulonner
V60.200



Eclisse à
boulonner
V35.200