


TFCL85S

TFCL avec SIN



A fixer avec:



Eclisse à boulonner
V60.200

| Référence | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/m | 📦 | Unité |
|--------------------------|---------|---------|------------|---------|-------|----|-------|
| TFCL85.100.200S12 | 85 | 100 | 2 | 3000 | 5,110 | 30 | M |
| TFCL85.100.200S13 | 85 | 100 | 2 | 3000 | 5,110 | 30 | M |
| TFCL85.150.200S12 | 85 | 150 | 2 | 3000 | 5,910 | 30 | M |
| TFCL85.150.200S13 | 85 | 150 | 2 | 3000 | 5,910 | 30 | M |
| TFCL85.150.200S23 | 85 | 150 | 2 | 3000 | 6,590 | 30 | M |
| TFCL85.200.200S12 | 85 | 200 | 2 | 3000 | 6,710 | 30 | M |
| TFCL85.200.200S13 | 85 | 200 | 2 | 3000 | 6,710 | 30 | M |
| TFCL85.200.200S23 | 85 | 200 | 2 | 3000 | 7,390 | 30 | M |
| TFCL85.250.200S12 | 85 | 250 | 2 | 3000 | 7,510 | 30 | M |
| TFCL85.250.200S13 | 85 | 250 | 2 | 3000 | 7,510 | 30 | M |
| TFCL85.250.200S23 | 85 | 250 | 2 | 3000 | 8,190 | 30 | M |
| TFCL85.300.200S12 | 85 | 300 | 2 | 3000 | 8,310 | 30 | M |
| TFCL85.300.200S13 | 85 | 300 | 2 | 3000 | 8,310 | 30 | M |
| TFCL85.300.200S23 | 85 | 300 | 2 | 3000 | 8,990 | 30 | M |

S12: 1 cloison de séparation séparée au milieu

S13: 1 cloison de séparation séparée sur 1/3 du bord

S23: 2 cloisons de séparation séparée sur 1/3 du bord