

## KLLVB

### Courbe extérieure pour KLL



A fixer avec:



Boulon et écrou autobloquant  
VM

Rayon: 300 mm

| Référence             | Finition | ↑<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Unité |
|-----------------------|----------|---------|---------|------------|---------|--------|---|-------|
| <b>KLLVB60.150</b>    | -        | 60      | 146     |            |         | 1,528  | 1 | STK   |
| <b>KLLVB60.200</b>    | -        | 60      | 196     |            |         | 1,629  | 1 | STK   |
| <b>KLLVB60.300</b>    | -        | 60      | 296     |            |         | 1,830  | 1 | STK   |
| <b>KLLVB60.400</b>    | -        | 60      | 396     |            |         | 2,032  | 1 | STK   |
| <b>KLLVB60.450</b>    | -        | 60      | 443     |            |         | 2,133  | 1 | STK   |
| <b>KLLVB60.500</b>    | -        | 60      | 496     |            |         | 2,234  | 1 | STK   |
| <b>KLLVB60.600</b>    | -        | 60      | 596     |            |         | 2,435  | 1 | STK   |
| <b>KLLVB60.750</b>    | SZ       | 60      | 750     | 1,25       |         | 2,501  | 1 | STK   |
| <b>KLLVB60.800</b>    | SZ       | 60      | 800     | 1,25       |         | 2,588  | 1 | STK   |
| <b>KLLVB60.900</b>    | SZ       | 60      | 900     | 1,25       |         | 2,762  | 1 | STK   |
| <b>KLLVB110.150</b>   | -        | 110     | 145     |            |         | 2,934  | 1 | STK   |
| <b>KLLVB110.200</b>   | -        | 110     | 196     |            |         | 2,755  | 1 | STK   |
| <b>KLLVB110.300</b>   | -        | 110     | 296     |            |         | 2,956  | 1 | STK   |
| <b>KLLVB110.400</b>   | -        | 110     | 396     |            |         | 3,158  | 1 | STK   |
| <b>KLLVB110.450</b>   | -        | 110     | 445     |            |         | 3,259  | 1 | STK   |
| <b>KLLVB110.500</b>   | -        | 110     | 496     |            |         | 3,360  | 1 | STK   |
| <b>KLLVB110.600</b>   | -        | 110     | 596     |            |         | 3,561  | 1 | STK   |
| <b>KLLVB110.750</b>   | -        | 110     | 750     |            |         | 3,863  | 1 | STK   |
| <b>KLLVB110.800</b>   | SZ       | 110     | 800     | 1,25       |         | 3,549  | 1 | STK   |
| <b>KLLVB110.900</b>   | -        | 110     | 900     |            |         | 4,165  | 1 | STK   |
| <b>ZMKLLVB60.150</b>  | DF       | 60      | 150     | 1,25       |         | 1,455  | 1 | STK   |
| <b>ZMKLLVB60.200</b>  | DF       | 60      | 200     | 1,25       |         | 1,542  | 1 | STK   |
| <b>ZMKLLVB60.300</b>  | DF       | 60      | 300     | 1,25       |         | 1,716  | 1 | STK   |
| <b>ZMKLLVB60.400</b>  | DF       | 60      | 400     | 1,25       |         | 1,891  | 1 | STK   |
| <b>ZMKLLVB60.450</b>  | DF       | 60      | 450     | 1,25       |         | 1,978  | 1 | STK   |
| <b>ZMKLLVB60.500</b>  | DF       | 60      | 500     | 1,25       |         | 2,065  | 1 | STK   |
| <b>ZMKLLVB60.600</b>  | DF       | 60      | 600     | 1,25       |         | 2,239  | 1 | STK   |
| <b>ZMKLLVB60.750</b>  | DF       | 60      | 750     | 1,25       |         | 2,501  | 1 | STK   |
| <b>ZMKLLVB60.800</b>  | DF       | 60      | 800     | 1,25       |         | 2,588  | 1 | STK   |
| <b>ZMKLLVB60.900</b>  | DF       | 60      | 900     | 1,25       |         | 2,762  | 1 | STK   |
| <b>ZMKLLVB110.150</b> | DF       | 110     | 150     | 1,25       |         | 2,416  | 1 | STK   |
| <b>ZMKLLVB110.200</b> | DF       | 110     | 200     | 1,25       |         | 2,503  | 1 | STK   |
| <b>ZMKLLVB110.300</b> | DF       | 110     | 300     | 1,25       |         | 2,677  | 1 | STK   |
| <b>ZMKLLVB110.400</b> | DF       | 110     | 400     | 1,25       |         | 2,851  | 1 | STK   |
| <b>ZMKLLVB110.450</b> | DF       | 110     | 450     | 1,25       |         | 2,939  | 1 | STK   |
| <b>ZMKLLVB110.500</b> | DF       | 110     | 500     | 1,25       |         | 3,026  | 1 | STK   |
| <b>ZMKLLVB110.600</b> | DF       | 110     | 600     | 1,25       |         | 3,200  | 1 | STK   |
| <b>ZMKLLVB110.750</b> | DF       | 110     | 750     | 1,25       |         | 3,462  | 1 | STK   |
| <b>ZMKLLVB110.800</b> | DF       | 110     | 800     | 1,25       |         | 3,549  | 1 | STK   |
| <b>ZMKLLVB110.900</b> | DF       | 110     | 900     | 1,25       |         | 3,723  | 1 | STK   |

Nombre minimal des boulons et des écrous VM6.10: 8 pièces.

#### Légende de la finition

- SZ = Sendzimir
- DF = Defender